



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G540 (2.66 GHz Intel Xeon Processor X5355)

SPECint_rate2000 = 198

SPECint_rate_base2000 = 197

SPEC license #: 97 Tested by: Acer Incorporated Test date: Dec-2006 Hardware Avail: Nov-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	89.7	145	8	89.7	145
175.vpr	8	91.9	141	8	90.8	143
176.gcc	8	56.6	180	8	56.6	180
181.mcf	8	123	136	8	123	136
186.crafty	8	41.0	226	8	41.0	226
197.parser	8	95.3	175	8	95.1	176
252.eon	8	37.9	319	8	37.5	321
253.perlbnk	8	59.4	281	8	59.7	280
254.gap	8	71.6	142	8	71.6	142
255.vortex	8	52.7	335	8	52.7	335
256.bzip2	8	94.6	147	8	93.7	149
300.twolf	8	99.3	280	8	99.3	280

Hardware

CPU: Intel Xeon Processor X5355 (2.66 GHz, 8MB L2, 1333MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1
Compiler: Intel C++ Compiler 9.1 Build 20060323Z for IA32
Microsoft Visual Studio .Net 2003 (7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G540 (2.66 GHz Intel Xeon Processor X5355)

SPECint_rate2000 = 198

SPECint_rate_base2000 = 197

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2006 | Hardware Avail: Nov-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib

Enable hardware prefetching and disable adjacent cache line prefetch BIOS setting