



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation
IBM BladeCenter LS41 (AMD Opteron 8220)

SPECint_rate2000 = 164
SPECint_rate_base2000 = 144

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Feb-2007 | Hardware Avail: Feb-2007 | Software Avail: Oct-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	83.8	155	8	83.6	155
175.vpr	8	117	111	8	110	118
176.gcc	8	63.9	160	8	64.1	159
181.mcf	8	343	48.6	8	198	84.5
186.crafty	8	42.4	219	8	42.1	220
197.parser	8	163	103	8	123	136
252.eon	8	43.9	275	8	39.4	306
253.perlbnk	8	104	161	8	88.7	188
254.gap	8	66.6	153	8	65.3	156
255.vortex	8	77.0	229	8	70.1	251
256.bzip2	8	105	133	8	105	133
300.twolf	8	226	123	8	165	169

Hardware

CPU: AMD Opteron 8220
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
CPU(s) orderable: 1,2,3,4 chips
Parallel: No
Primary Cache: 64 KB I + 64 KB D on chip (per core)
Secondary Cache: 1 MB I+D on chip (per core)
L3 Cache: N/A
Other Cache: N/A
Memory: 32 GB (15x2 GB PC2-5300)
Disk Subsystem: 1x73 GB 10K SAS
Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 3
SuSE kernel 2.6.5-7.244-default
Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.5
File System: Linux/ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
           -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO
176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
         -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation
IBM BladeCenter LS41 (AMD Opteron 8220)

SPECint_rate2000 = 164
SPECint_rate_base2000 = 144

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Feb-2007 | Hardware Avail: Feb-2007 | Software Avail: Oct-2006

Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```