

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Dell Computer Corporation: PowerEdge 2400/667
Microsoft: Internet Information Server 5.0

SPECweb99 = 732
Test Date: Mar-2000
Tester: Dell

Hardware Avail: Feb-2000 OS Avail: Feb-2000 HTTP Software Avail: Feb-2000 Sup. Software Avail: -- SPEC license #: 55

Hardware

Vendor: Dell Computer Corporation
Model: PowerEdge 2400/667
Processor: 667MHz Pentium III
Processors: 1 core, 1 chip, 1 core/chip
Primary Cache: 16KBI+16KBD on chip
Secondary Cache: 256KB(I+D) on chip
Other Cache: None
Memory: 2 GB
Disk Subsystem: 5 9GB 10KRPM drives
Disk Controllers: Onboard PERC2/Si RAID
Other Hardware: 1 Alteon ACEswitch 180

Software

Operating System: Windows 2000 Advanced Server
File System: NTFS
Other Software: None

HTTP Software

Vendor: Microsoft
HTTP Software: Internet Information Server 5.0
API: ISAPI
Server Cache: None
Log Mode: W3C Extended Log File Format

Test Sponsor

Test Date: Mar-2000
Tested By: Dell
SPEC License: 55

Network

of Controllers: 1
Network Controllers: Alteon AceNIC PCI
of Nets: 1
Type of Nets: Gigabit Ethernet
Network Speed: 1Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 5
Model: Dell Precision 410
Processor: 450MHz Pentium II
of Processors: 2
Memory: 128MB
Network Controller: Alteon AceNIC PCI
Operating System: Windows 2000 Professional
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

IIS settings: maximum performance.
IIS Home Directory: Access for Read & Write, Scripts & Executables.
IIS Virtual Directory spec99 points back to web server root, low application protection.
IIS Logging: W3C Extended logging, defaults plus bytes sent.

Operating System Notes

Tuning parameters:
- Tcpip/Parameters/MaxHashTableSize=0x10000, sets TCB hash table size to 65,536 entries, default is 512.
- Tcpip/Parameters/TcpTimedWaitDelay=0x3c, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default is 240.
- Tcpip/Parameters/MaxFreeTwTcbs=400000, sets maximum number of TIME_WAIT tcbs to 400,000.
- Tcpip/Parameters/MaxUserPort = 0xffffe, sets maximum open ports to 65534.
- Tcpip/Parameters/TcpWindowSize = 17520, sets TCP send/receive window size, default 8192.
- Tcpip/Parameters/NumTcbTablePartitions = 16, sets number of independent TCB table segments, default 4.
- Inetinfo/Parameters/ObjectCacheTTL=0xfffff, sets IIS object cache timeout, default 10 minutes
- Inetinfo/Parameters/ListenBacklog=1000, default 25.
- Inetinfo/Parameters/AcceptExTimeout=1, sets time for accept ex socket to wait for receive, default 120.
- Inetinfo/Parameters/LogFileFlushInterval=60, forces flush every 60 seconds, default 300.
- Inetinfo/Parameters/MaxPoolThreads=20, maximum network request threads per processor, default 10.
- Inetinfo/Parameters/PoolThreadLimit=20, maximum pool threads in system, default 2*#MB.
Alteon NIC settings in registry:
- StatTicks=0, default 100000.
- SendCoalTicks=10000, sets number of microsec before send buffers are returned to host, default 100000.
- RecvCoalTicks=10000, sets number of microsec before recv buffers are given to host, default 100000.
- RecvCoalMax=80, sets number of frames received before notifying host, default 20.
- RxFlowControl=0 (off), default 1.

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP API Notes

Microsoft ISAPI for IIS 5.0 compiled with VC++ 6.0, code optimization = Pentium Pro.

Hardware Notes

One 9GB 10KRPM disk for OS, paging and logs, 4 9GB 10KRPM disks striped for web pages.