

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: RS/6000 7026-M80
Zeus Technology Ltd.: Zeus 3.3.5

SPECweb99 = 3216

Test Date: Apr-2000
Tester: IBM

Hardware Avail: Jun-2000 OS Avail: May-2000 HTTP Software Avail: Apr-2000 Sup. Software Avail: May-2000 SPEC license #: 11

Hardware

Vendor: IBM
Model: RS/6000 7026-M80
Processor: 500MHz RS64 III
Processors: 8 cores, 8 chips, 1 core/chip
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 4MB(I+D) off chip
Other Cache: None
Memory: 24 GB
Disk Subsystem: 2x9.1GB 16Bit SCSI Disk
2x18.2 SSA Logical Disk
Disk Controllers: Wide/Ultra-2 SCSI I/O Controller
IBM SSA 160 SerialRAID Adapter
Other Hardware: 3 x Alteon ACESwitch 180

Software

Operating System: AIX 4.3.3 + APAR IY09807
File System: JFS
Other Software: None

HTTP Software

Vendor: Zeus Technology Ltd.
HTTP Software: Zeus 3.3.5
API: Zeus ISAPI
Server Cache: N/A
Log Mode: Common Log Format

Test Sponsor

Test Date: Apr-2000
Tested By: IBM
SPEC License: 11

Network

of Controllers: 8
Network Controllers: 8 Gigabit Ethernet-SX PCI Adapter
of Nets: 8
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gigabit/sec
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 16
Model: RS/6000 43P-260
Processor: 200 MHz POWER3
of Processors: 2
Memory: 1024MB
Network Controller: 1 Gigabit Ethernet-SX PCI Adapter
Operating System: AIX 4.3.2
Compiler: IBM Cset++ Version 3.1.3

Notes/Tuning Information

SUT Notes

APAR IY09807: New hardware support for May-2000
no(network option) tuning:
no -o send_file duration=180000(cached send_file expiration time, default=300)
somaxconn=8192(max listen backlog, default=1024)
nbc_max_cache=131072(max file size for network buffer cache,default=1048576)
nbc_pseg=20000(max file entries in private segment,default=0)
tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
Processor affinity - bind 8 Ethernet interrupts to 8 cpu's(1 interrupt to 1 cpu)
maxpgahead=56(the maximum number of pages to be read ahead,default=28)
maxfree=296(the number of frames on the free list at which page stealing is to stop,default=256)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
Used 1 external 7026-F/C6324 I/O drawer (4 adapters each).
Used 1 external 7026-F/C6325 I/O drawer (4 adapters each).

Client Notes

no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={80}(delay ack ports,default={ })
tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)

Other Notes

Zeus 3.3.5 tuning:
global.cfg:
errlog %zeushome%/web/log/errors

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Other Notes (Continued)

gid system
uid root
controlport 9080
controlallow 127.0.0.1
tuning!bind_any no
tuning!cache_files 100001
tuning!cache_large_file 1048576
tuning!cache_small_file 4096
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 7200
tuning!cache_max_bytes 0
tuning!num_children 9
tuning!keepalive yes
tuning!listen_queue_size 8192
tuning!multiple_accept yes
tuning!sendfile yes
tuning!sendfile_maxsize 307200
tuning!sendfile_minsize 4096
tuning!sendfile_reservefd 13999
tuning!so_nagle_off no
tuning!so_rbuff_size 16384
tuning!so_wbuff_size 16384
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll yes