

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company: HP ProLiant DL145 G2
Zeus Technology Limited: Zeus V4.2r4 (64-bit)

SPECweb99_SSL =4300

Test Date: Aug-2005
Tester: Hewlett-Packard Company

Hardware Avail: Sep-2005 OS Avail: Jan-2005 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Apr-2005 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard Company
Model: HP ProLiant DL145 G2
Processor: AMD Opteron 280, 2.4GHz
Processors: 4 cores, 2 chips, 2 cores/chip
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1MB (on chip) per core
Other Cache: none
Memory: 16GB (8x2GB PC3200 DDR)
Disk Subsystem: 2x80GB SATA 7200 rpm HDD
Disk Controllers: Integrated 2-port Serial ATA Controller
Other Hardware: HP ProCurve 2848 switch

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP2
File System: ext2
Other Software: none

HTTPS Software

Vendor: Zeus Technology Limited
HTTPS Software: Zeus V4.2r4 (64-bit)
API: Zeus PEPP 0.9pre1 ISAPI for dynamic content
Server Cache: none
Log Mode: Binary Common Log Format

Test Sponsor

Test Date: Aug-2005
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 2
Network Controllers: NC7782
of Nets: 2
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 6
Model: HP ProLiant DL360 G3
Processor: 3.60GHz 1MB L3 cache Intel Xeon
of Processors: 2 cores, 2 chips, 1 core/chip
Memory: 4096MB
Network Controller: 2xIntegrated NC7781
Operating System: Windows Server 2003 Std. Edition
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

- 1 drive used for OS and access logs
- 1 drive used for the workload files

Operating System Notes

Filesystem mounted with noatime,nodiratime, noacl - no inode access time updateing, no access control lists
irq_balancer daemon disabled, default enabled

Each NIC IRQ bound to two seperate logical CPU, default round-robin

Each NIC's TX queue length set to 40000, default 100

ulimit -n 127015, sets number of open files, default 1024

1 > /proc/sys/net/ipv4/conf/all/rp_filter #enables source route verification, default 0

2000000 > /proc/sys/net/ipv4/tcp_max_tw_buckets #sets TCP time-wait buckets pool size, default 180000

30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_rmem #maximum TCP read-buffer space allocatable, default 4096 87380 174760

30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_wmem #maximum TCP write-buffer space allocatable, default 4096 16384 131072

30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_mem #maximum TCP buffer space allocatable, default 31744 32256 32768

10000000 > /proc/sys/net/core/rmem_max #maximum receive socket buffer size, default 65535

10000000 > /proc/sys/net/core/rmem_default #default receive socket buffer size, default 65535

10000000 > /proc/sys/net/core/wmem_max #maximum send socket buffer size, default 65535

10000000 > /proc/sys/net/core/wmem_default #default send socket buffer size, default 65535

10000000 > /proc/sys/net/core/optmem_max #default 10240

509059 > /proc/sys/fs/file-max #maximum number of open files, default 1024

TSO turned off for all NIC ports #TCP Segmentation Offload, default on

Timer IRQ bound to logical processors #0, default round-robin

Storage IRQ bound to logical processors #1, default round-robin

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

tuning!cache_cooling_time 0
tuning!cache_files 282011
tuning!cache_flush_interval 31536000
tuning!cache_max_bytes 0
tuning!cache_stat_expire 31536000
tuning!cbuff_size 65536
tuning!clientfirst_optimise yes
tuning!isapi!enabled yes
tuning!keepalive_max -1
tuning!keepalive_timeout 30
tuning!listen_queue_size 8192
tuning!maxaccept 2500
tuning!modules!cgi!cleansize 0
tuning!modules!cgi!enabled yes
tuning!modules!security!enabled yes
tuning!modules!stats!enabled no
tuning!sendfile yes
tuning!sendfile_minsize 1
tuning!so_rbuff_size 0
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!ssl_sessioncache_size 7507
tuning!unique_bind no
See HP-20030414-tunings.txt for a description of the Zeus tuning parameters

HTTP API Notes

Dynamic API: HP-20020724-API.tgz
Zeus PEPP configured with the ./Configure --ssl=yes

Client Notes

The alternate performance neutral alt.Win32 client was used.
Tcpip\Parameters\MaxUserPort=0xffff, sets maximum open ports to 65534
Tcpip\Parameters\TcpTimedWaitDelay=60, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default 240
Tcpip\Parameters\MaxFreeTwtcb=100000, sets maximum number of TIME_WAIT tcbs to 100,000
Tcpip\Parameters\TcpWindowSize=65535, sets TCP receive window size, default 8192

Other Notes

Server kernel: default SLES 9 SP2 (2.6.5-7.187-smp)