



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp®\_rate2006 = 36.5

NovaScale B260 (Intel Xeon processor 5150,2.66GHz)

SPECfp\_rate\_base2006 = 36.0

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Dec-2006

Hardware Availability: Dec-2006

Software Availability: Dec-2006



### Hardware

CPU Name: Intel Xeon 5150  
 CPU Characteristics: 2.66 GHz, 4MB L2, 1333MHz bus  
 CPU MHz: 2660  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1 to 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits) Service Pack1  
 Compiler: Intel C++ Compiler for IA32 version 9.1  
 Package ID W\_CC\_C\_9.1.033 Build no 20061103Z  
 Intel Fortran Compiler for IA32 version 9.1  
 Package ID W\_FC\_C\_9.1.033 Build no 20061103Z  
 Microsoft Visual Studio .NET 2003 (lib & linker)  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp\_rate2006 = 36.5

NovaScale B260 (Intel Xeon processor 5150,2.66GHz)

SPECfp\_rate\_base2006 = 36.0

CPU2006 license: 20

Test date: Dec-2006

Test sponsor: Bull SAS

Hardware Availability: Dec-2006

Tested by: Bull SAS

Software Availability: Dec-2006

L3 Cache: None  
 Other Cache: None  
 Memory: 8 GB (2GB DIMMx4, FB-DIMM PC2-5300F ECC CL5)  
 Disk Subsystem: 73 GB SAS, 10000RPM  
 Other Hardware: None

Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: MicroQuill SmartHeap Library 8.0 (shIW32M.lib)

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	4	1883	28.9	1878	28.9	<b>1878</b>	<b>28.9</b>	4	<b>1875</b>	<b>29.0</b>	1874	29.0	1895	28.7		
416.gamess	4	1247	62.8	1247	62.8	<b>1247</b>	<b>62.8</b>	4	1251	62.6	<b>1250</b>	<b>62.6</b>	1250	62.6		
433.milc	4	2027	18.1	2034	18.1	<b>2030</b>	<b>18.1</b>	4	2022	18.2	2031	18.1	<b>2025</b>	<b>18.1</b>		
434.zeusmp	4	875	41.6	869	41.9	<b>870</b>	<b>41.8</b>	4	898	40.5	<b>899</b>	<b>40.5</b>	899	40.5		
435.gromacs	4	473	60.4	471	60.7	<b>471</b>	<b>60.6</b>	4	469	60.9	467	61.1	<b>469</b>	<b>60.9</b>		
436.cactusADM	4	1035	46.2	1034	46.2	<b>1034</b>	<b>46.2</b>	4	<b>1045</b>	<b>45.7</b>	1045	45.7	1045	45.7		
437.leslie3d	4	1882	20.0	<b>1883</b>	<b>20.0</b>	1883	20.0	4	1883	20.0	<b>1883</b>	<b>20.0</b>	1882	20.0		
444.namd	4	597	53.7	594	54.0	<b>594</b>	<b>54.0</b>	4	588	54.6	585	54.8	<b>585</b>	<b>54.8</b>		
447.dealII	4	736	62.2	726	63.0	<b>729</b>	<b>62.7</b>	4	<b>694</b>	<b>66.0</b>	670	68.3	700	65.4		
450.soplex	4	1482	22.5	1395	23.9	<b>1396</b>	<b>23.9</b>	4	1477	22.6	1389	24.0	<b>1391</b>	<b>24.0</b>		
453.povray	4	281	75.6	<b>281</b>	<b>75.8</b>	281	75.8	4	224	95.0	<b>223</b>	<b>95.2</b>	223	95.2		
454.calculix	4	<b>707</b>	<b>46.7</b>	696	47.4	715	46.1	4	697	47.3	<b>697</b>	<b>47.4</b>	691	47.8		
459.GemsFDTD	4	2270	18.7	2265	18.7	<b>2265</b>	<b>18.7</b>	4	2276	18.6	2279	18.6	<b>2277</b>	<b>18.6</b>		
465.tonto	4	1185	33.2	1204	32.7	<b>1198</b>	<b>32.9</b>	4	1250	31.5	1174	33.5	<b>1192</b>	<b>33.0</b>		
470.lbm	4	<b>3488</b>	<b>15.8</b>	3488	15.8	3486	15.8	4	<b>3467</b>	<b>15.9</b>	3468	15.8	3466	15.9		
481.wrf	4	1257	35.5	1244	35.9	<b>1246</b>	<b>35.8</b>	4	1265	35.3	1261	35.4	<b>1261</b>	<b>35.4</b>		
482.sphinx3	4	2104	37.1	2092	37.3	<b>2096</b>	<b>37.2</b>	4	2152	36.2	2144	36.4	<b>2145</b>	<b>36.3</b>		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Base Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp\_rate2006 = 36.5

NovaScale B260 (Intel Xeon processor 5150,2.66GHz)

SPECfp\_rate\_base2006 = 36.0

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Dec-2006  
Hardware Availability: Dec-2006  
Software Availability: Dec-2006

## Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
-DBOOST\_NO\_INTRINSIC\_WCHAR\_T  
453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Base Optimization Flags

C benchmarks:  
-fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:  
-fast -Qcxx\_features /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:  
-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:  
-fast /F950000000 -link /FORCE:MULTIPLE

## Peak Compiler Invocation

C benchmarks:  
icl -Qvc7.1 -Qc99

C++ benchmarks:  
icl -Qvc7.1

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icl -Qvc7.1 -Qc99 ifort

## Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
-DBOOST\_NO\_INTRINSIC\_WCHAR\_T

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

SPECfp\_rate2006 = 36.5

NovaScale B260 (Intel Xeon processor 5150,2.66GHz)

SPECfp\_rate\_base2006 = 36.0

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: Dec-2006  
Hardware Availability: Dec-2006  
Software Availability: Dec-2006

## Peak Portability Flags (Continued)

453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Peak Optimization Flags

C benchmarks:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F950000000 shlw32m.lib  
-link /FORCE:MULTIPLE

C++ benchmarks:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qcxx\_features  
/F950000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F950000000  
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F950000000  
-link /FORCE:MULTIPLE

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 10:19:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 6 February 2007.