



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## SPECint®\_rate2006 = Not Run

## IBM System x3850 (Intel Xeon 7150N)

## SPECint\_rate\_base2006 = 66.9

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Aug-2006



### Hardware

CPU Name: Intel Xeon 7150N  
 CPU Characteristics: 667 MHz bus  
 CPU MHz: 3500  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2,4 chips  
 Primary Cache: 12 K micro-ops I + 16 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 16 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 32 GB (16 x 2048 MB ECC PC2-3200)  
 Disk Subsystem: 73 GB SAS, 10k RPM  
 Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)  
 Compiler: Intel C++ Compiler for IA32 version 9.1  
 Build no 20060816  
 Microsoft Visual Studio .Net 2003 (for libraries)  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: Not Applicable  
 Other Software: Smart Heap Library, Version 8



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = Not Run

IBM System x3850 (Intel Xeon 7150N)

SPECint\_rate\_base2006 = 66.9

CPU2006 license: 11

Test date: Feb-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
400.perlbench	16	1578	99.0	<b>1577</b>	<b>99.1</b>	1576	99.2									
401.bzip2	16	1683	91.7	1681	91.8	<b>1681</b>	<b>91.8</b>									
403.gcc	16	5286	24.4	5332	24.2	<b>5296</b>	<b>24.3</b>									
429.mcf	16	2198	66.4	<b>2198</b>	<b>66.4</b>	2198	66.4									
445.gobmk	16	1848	90.8	<b>1847</b>	<b>90.9</b>	1845	91.0									
456.hammer	16	2195	68.0	2193	68.1	<b>2193</b>	<b>68.1</b>									
458.sjeng	16	2691	71.9	2776	69.7	<b>2691</b>	<b>71.9</b>									
462.libquantum	16	<b>13276</b>	<b>25.0</b>	13279	25.0	13272	25.0									
464.h264ref	16	2050	173	<b>2050</b>	<b>173</b>	2047	173									
471.omnetpp	16	<b>2691</b>	<b>37.2</b>	2690	37.2	2692	37.2									
473.astar	16	1413	79.5	1404	80.0	<b>1408</b>	<b>79.8</b>									
483.xalancbmk	16	<b>1142</b>	<b>96.7</b>	1143	96.6	1141	96.8									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

### Bios Settings

Hardware Prefetch enabled

Memory Array set to High-Performance Memory Array

## Base Compiler Invocation

### C benchmarks:

icl -Qvc7.1 -Qc99

### C++ benchmarks:

icl -Qvc7.1

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Base Optimization Flags

### C benchmarks:

-fast /F512000000 shlw32m.lib

-link /FORCE:MULTIPLE

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = Not Run

IBM System x3850 (Intel Xeon 7150N)

SPECint\_rate\_base2006 = 66.9

CPU2006 license: 11

Test date: Feb-2007

Test sponsor: IBM Corporation

Hardware Availability: Jan-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

## Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090715.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090715.01.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 10:34:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 6 March 2007.