



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp[®]_rate2006 = 37.8

Servidor Itautec MX201 (Intel Xeon E5310)

SPECfp_rate_base2006 = 37.8

CPU2006 license: 9001


Test sponsor: Itautec

Tested by: Itautec

Test date: Feb-2007

Hardware Availability: Feb-2007

Software Availability: May-2006



Hardware

CPU Name: Intel Xeon E5310
 CPU Characteristics: 1066MHz system bus
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1-2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler for IA32 version 9.1
 Package ID W_CC_C_9.1.025 Build no 20060519Z
 Intel Fortran Compiler for IA32 version 9.1
 Package ID W_FC_C_9.1.025 Build no 20060519Z
 Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries)
 Auto Parallel: No
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp_rate2006 = 37.8

Servidor Itaotec MX201 (Intel Xeon E5310)

SPECfp_rate_base2006 = 37.8

CPU2006 license: 9001
Test sponsor: Itaotec
Tested by: Itaotec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1GB DDR2-RAM PC2-5300F CAS 5-5-5)
Disk Subsystem: 73 GB SCSI, 10000RPM
Other Hardware: None

System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: Microquill SmartHeap Library v.8.0 for SMP

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	4301	25.3	4299	25.3	4304	25.3	8	4301	25.3	4299	25.3	4304	25.3
416.gamess	8	2059	76.1	2058	76.1	2059	76.1	8	2059	76.1	2058	76.1	2059	76.1
433.milc	8	4948	14.8	4942	14.9	4947	14.8	8	4948	14.8	4942	14.9	4947	14.8
434.zeusmp	8	1536	47.4	1537	47.4	1539	47.3	8	1536	47.4	1537	47.4	1539	47.3
435.gromacs	8	791	72.2	790	72.3	791	72.2	8	791	72.2	790	72.3	791	72.2
436.cactusADM	8	2492	38.4	2493	38.3	2492	38.4	8	2492	38.4	2493	38.3	2492	38.4
437.leslie3d	8	4057	18.5	4050	18.6	4055	18.5	8	4057	18.5	4050	18.6	4055	18.5
444.namd	8	1004	63.9	996	64.4	996	64.4	8	1004	63.9	996	64.4	996	64.4
447.dealII	8	1181	77.5	1203	76.1	1231	74.3	8	1181	77.5	1203	76.1	1231	74.3
450.soplex	8	3027	22.0	3033	22.0	3028	22.0	8	3027	22.0	3033	22.0	3028	22.0
453.povray	8	469	90.7	469	90.7	469	90.7	8	469	90.7	469	90.7	469	90.7
454.calculix	8	1141	57.9	1154	57.2	1153	57.3	8	1141	57.9	1154	57.2	1153	57.3
459.GemsFDTD	8	5162	16.4	5159	16.5	5155	16.5	8	5162	16.4	5159	16.5	5155	16.5
465.tonto	8	1964	40.1	1927	40.9	1964	40.1	8	1964	40.1	1927	40.9	1964	40.1
470.lbm	8	5425	20.3	5422	20.3	5419	20.3	8	5425	20.3	5422	20.3	5419	20.3
481.wrf	8	2499	35.8	2495	35.8	2508	35.6	8	2499	35.8	2495	35.8	2508	35.6
482.sphinx3	8	4335	36.0	4339	35.9	4337	36.0	8	4335	36.0	4339	35.9	4337	36.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Servidor Itaotec MX221.
The Servidor Itaotec MX221 and the Servidor Itaotec MX201
are electronically equivalent.

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 37.8

Servidor Itautec MX201 (Intel Xeon E5310)

SPECfp_rate_base2006 = 37.8

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc7.1 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-DBOOST_NO_INTRINSIC_WCHAR_T
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:
-fast /F950000000 shlSMPMt.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-fast -Qcxx_features /F950000000 shlSMPMt.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:
-fast /F950000000 -link /FORCE:MULTIPLE

Peak Optimization Flags

C benchmarks:
433.milc: basepeak = yes
470.lbm: basepeak = yes
482.sphinx3: basepeak = yes

C++ benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 37.8

Servidor Itautec MX201 (Intel Xeon E5310)

SPECfp_rate_base2006 = 37.8

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: basepeak = yes

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:44:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 March 2007.