



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECint®2006 = 16.0

SPECint_base2006 = 15.4

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5150
 CPU Characteristics: 2.66 GHz, 4 MB L2, 1333 MHz system bus
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 to 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
 Disk Subsystem: 1x73 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition X64 Edition Service Pack 1
 Compiler: Intel C++ Compiler for IA32 version 9.1
 Package ID W_CC_C_9.1.033 Build no 20061103Z
 Microsoft Visual Studio .NET 2003 (lib & linker)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: MicroQuill SmartHeap Library 8.0 (shIW32M.lib)



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECint2006 = 16.0

SPECint_base2006 = 15.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	513	19.1	511	19.1	<u>511</u>	<u>19.1</u>	469	20.8	470	20.8	<u>470</u>	<u>20.8</u>
401.bzip2	709	13.6	711	13.6	<u>710</u>	<u>13.6</u>	691	14.0	<u>691</u>	<u>14.0</u>	691	14.0
403.gcc	761	10.6	<u>762</u>	<u>10.6</u>	763	10.6	743	10.8	745	10.8	<u>745</u>	<u>10.8</u>
429.mcf	512	17.8	<u>512</u>	<u>17.8</u>	512	17.8	550	16.6	<u>550</u>	<u>16.6</u>	549	16.6
445.gobmk	604	17.4	604	17.4	<u>604</u>	<u>17.4</u>	535	19.6	<u>535</u>	<u>19.6</u>	535	19.6
456.hammer	<u>837</u>	<u>11.2</u>	837	11.2	837	11.2	814	11.5	<u>814</u>	<u>11.5</u>	814	11.5
458.sjeng	753	16.1	<u>753</u>	<u>16.1</u>	753	16.1	694	17.4	<u>693</u>	<u>17.5</u>	693	17.5
462.libquantum	1396	14.8	1399	14.8	<u>1397</u>	<u>14.8</u>	1377	15.1	<u>1376</u>	<u>15.1</u>	1375	15.1
464.h264ref	<u>798</u>	<u>27.7</u>	798	27.7	798	27.7	779	28.4	<u>779</u>	<u>28.4</u>	779	28.4
471.omnetpp	532	11.8	530	11.8	<u>530</u>	<u>11.8</u>	485	12.9	<u>485</u>	<u>12.9</u>	485	12.9
473.astar	563	12.5	562	12.5	<u>563</u>	<u>12.5</u>	561	12.5	<u>561</u>	<u>12.5</u>	561	12.5
483.xalancbmk	353	19.5	<u>353</u>	<u>19.5</u>	353	19.5	349	19.8	349	19.8	<u>349</u>	<u>19.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment

General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.
The results have been measured on a NovaScale R460 model.

Base Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECint2006 = 16.0

SPECint_base2006 = 15.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECint2006 = 16.0

SPECint_base2006 = 15.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:47:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.