



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor E5345)

SPECfp[®]_rate2006 = 55.5

SPECfp_rate_base2006 = 53.6

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007



Hardware

CPU Name: Intel Xeon E5345
 CPU Characteristics: 2.33 GHz, 2x4 MB L2 shared, 1333 MHz bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp for x86_64
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package-ID: l_cc_c_9.1.049
 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package-ID: l_fc_c_9.1.045
 Auto Parallel: No
 File System: ext2

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor E5345)

SPECfp_rate2006 = 55.5

SPECfp_rate_base2006 = 53.6

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2007
Hardware Availability: Jan-2007
Software Availability: Jun-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB DDR2 5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x73.2 GB SAS, 15000RPM
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3448	31.5	3444	31.6	3448	31.5	8	3448	31.5	3444	31.6	3448	31.5
416.gamess	8	1229	127	1228	128	1231	127	8	1229	127	1228	128	1231	127
433.milc	8	3370	21.8	3368	21.8	3371	21.8	8	3515	20.9	3516	20.9	3515	20.9
434.zeusmp	8	1218	59.8	1217	59.8	1226	59.4	8	1204	60.5	1204	60.4	1204	60.5
435.gromacs	8	515	111	515	111	514	111	8	499	114	500	114	499	114
436.cactusADM	8	1437	66.5	1431	66.8	1440	66.4	8	1437	66.5	1431	66.8	1440	66.4
437.leslie3d	8	3281	22.9	3287	22.9	3295	22.8	8	3281	22.9	3287	22.9	3295	22.8
444.namd	8	658	97.6	658	97.5	658	97.5	8	658	97.6	658	97.5	658	97.5
447.dealII	8	787	116	784	117	781	117	8	772	119	771	119	771	119
450.soplex	8	2268	29.4	2264	29.5	2263	29.5	8	2064	32.3	2066	32.3	2072	32.2
453.povray	8	337	126	337	126	333	128	8	251	169	252	169	252	169
454.calculix	8	716	92.2	718	91.9	714	92.4	8	699	94.5	698	94.6	704	93.8
459.GemsFDTD	8	3913	21.7	3906	21.7	3906	21.7	8	3913	21.7	3906	21.7	3906	21.7
465.tonto	8	1088	72.3	1091	72.1	1094	72.0	8	1063	74.1	1065	73.9	1056	74.6
470.lbm	8	4621	23.8	4621	23.8	4621	23.8	8	4351	25.3	4352	25.3	4350	25.3
481.wrf	8	1970	45.4	1973	45.3	1969	45.4	8	1970	45.4	1973	45.3	1969	45.4
482.sphinx3	8	3668	42.5	3671	42.5	3664	42.6	8	3395	45.9	3393	45.9	3385	46.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 1333 MHz

All binaries were built with 64-bit Intel compiler except:

433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with 32-bit Intel compiler by changing the path for include and library files.

The Express5800/120Rg-1(Intel Xeon processor E5345) and

the Express5800/120Ri-2(Intel Xeon processor E5345) models are electronically equivalent.

The results have been measured on a Express5800/120Ri-2(Intel Xeon processor E5345) model.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor E5345)

SPECfp_rate2006 = 55.5

SPECfp_rate_base2006 = 53.6

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor E5345)

SPECfp_rate2006 = 55.5

SPECfp_rate_base2006 = 53.6

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007

Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.049/bin/icc -I/opt/intel/cc/9.1.049/include  
-L/opt/intel/cc/9.1.049/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.049/bin/icpc  
-I/opt/intel/cc/9.1.049/include -L/opt/intel/cc/9.1.049/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.045/bin/ifort  
-I/opt/intel/fc/9.1.045/include -L/opt/intel/fc/9.1.045/lib
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.deallI: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast
```

```
470.lbm: Same as 433.milc
```

```
482.sphinx3: -fast
```

C++ benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor E5345)

SPECfp_rate2006 = 55.5

SPECfp_rate_base2006 = 53.6

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007

Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: -prof_gen(pass 1) -prof_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:

435.gromacs: -prof_gen(pass 1) -prof_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:22:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 July 2007.