



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp®2006 = 10.9

IBM System x3655 (AMD Opteron 2212)

SPECfp_base2006 = 10.4

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2007

Hardware Availability: Oct-2006

Software Availability: Mar-2007



SPECfp_base2006 = 10.4

SPECfp2006 = 10.9

Hardware

CPU Name: AMD Opteron 2212
 CPU Characteristics:
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

Software

Operating System: SLES 10 (x86_64), 2.6.16.21-0.8-smp
 Compiler: QLogic PathScale Compiler Suite, Release 3.0
 Auto Parallel: No
 File System: ext3
 System State: Multi-user, run level 3
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 10.9

IBM System x3655 (AMD Opteron 2212)

SPECfp_base2006 = 10.4

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jul-2007
Hardware Availability: Oct-2006
Software Availability: Mar-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2GB DDR2-5300 ECC)
Disk Subsystem: 1 x 36 GB SAS, 10000 RPM
Other Hardware: None

Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>932</u>	<u>14.6</u>	930	14.6	933	14.6	866	15.7	865	15.7	<u>866</u>	<u>15.7</u>
416.gamess	1940	10.1	1937	10.1	<u>1940</u>	<u>10.1</u>	1710	11.4	1706	11.5	<u>1707</u>	<u>11.5</u>
433.milc	915	10.0	<u>913</u>	<u>10.1</u>	909	10.1	<u>861</u>	<u>10.7</u>	862	10.7	856	10.7
434.zeusmp	<u>1008</u>	<u>9.03</u>	1007	9.03	1008	9.02	996	9.14	<u>997</u>	<u>9.13</u>	1000	9.10
435.gromacs	<u>798</u>	<u>8.94</u>	798	8.95	803	8.89	<u>705</u>	<u>10.1</u>	706	10.1	705	10.1
436.cactusADM	1169	10.2	1160	10.3	<u>1166</u>	<u>10.3</u>	<u>1152</u>	<u>10.4</u>	1161	10.3	1148	10.4
437.leslie3d	<u>942</u>	<u>9.98</u>	940	10.0	947	9.93	<u>942</u>	<u>9.98</u>	940	10.0	947	9.93
444.namd	917	8.75	918	8.73	<u>918</u>	<u>8.74</u>	<u>866</u>	<u>9.27</u>	865	9.27	866	9.26
447.dealII	795	14.4	<u>795</u>	<u>14.4</u>	796	14.4	722	15.8	<u>721</u>	<u>15.9</u>	720	15.9
450.soplex	982	8.49	<u>987</u>	<u>8.45</u>	987	8.45	881	9.47	875	9.53	<u>879</u>	<u>9.49</u>
453.povray	459	11.6	<u>459</u>	<u>11.6</u>	456	11.7	417	12.8	416	12.8	<u>417</u>	<u>12.8</u>
454.calculix	1536	5.37	<u>1536</u>	<u>5.37</u>	1536	5.37	1422	5.80	1421	5.80	<u>1422</u>	<u>5.80</u>
459.GemsFDTD	1027	10.3	<u>1028</u>	<u>10.3</u>	1029	10.3	1072	9.90	1083	9.80	<u>1073</u>	<u>9.89</u>
465.tonto	852	11.6	855	11.5	<u>853</u>	<u>11.5</u>	852	11.6	855	11.5	<u>853</u>	<u>11.5</u>
470.lbm	979	14.0	<u>1001</u>	<u>13.7</u>	1016	13.5	979	14.0	<u>1001</u>	<u>13.7</u>	1016	13.5
481.wrf	<u>929</u>	<u>12.0</u>	927	12.0	929	12.0	<u>929</u>	<u>12.0</u>	927	12.0	929	12.0
482.sphinx3	<u>1660</u>	<u>11.7</u>	1665	11.7	1654	11.8	<u>1660</u>	<u>11.7</u>	1665	11.7	1654	11.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

taskset utility used to bind CPU(s) to processes
DSPEC_CPU_TABLE_WORKAROUND was used for portability when compiling 447.dealII
due to compilation being performed on SLES 9 SP3

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 10.9

IBM System x3655 (AMD Opteron 2212)

SPECfp_base2006 = 10.4

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Base Compiler Invocation (Continued)

Fortran benchmarks:
pathf95

Benchmarks using both Fortran and C:
pathcc pathf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64
 436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64 -DSPEC_CPU_TABLE_WORKAROUND
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-Ofast

C++ benchmarks:
-Ofast

Fortran benchmarks:
-Ofast -OPT:malloc_alg=1

Benchmarks using both Fortran and C:
-Ofast -OPT:malloc_alg=1

Base Other Flags

C benchmarks:
-IPA:max_jobs=2

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 10.9

IBM System x3655 (AMD Opteron 2212)

SPECfp_base2006 = 10.4

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Base Other Flags (Continued)

C++ benchmarks:

-IPA:max_jobs=2

Fortran benchmarks:

-IPA:max_jobs=2

Benchmarks using both Fortran and C:

-IPA:max_jobs=2

Peak Compiler Invocation

C benchmarks:

pathcc

C++ benchmarks:

pathCC

Fortran benchmarks:

pathf95

Benchmarks using both Fortran and C:

pathcc pathf95

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64
 436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_TABLE_WORKAROUND
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
 482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 10.9

IBM System x3655 (AMD Opteron 2212)

SPECfp_base2006 = 10.4

CPU2006 license: 11

Test date: Jul-2007

Test sponsor: IBM Corporation

Hardware Availability: Oct-2006

Tested by: IBM Corporation

Software Availability: Mar-2007

Peak Optimization Flags

C benchmarks:

433.milc: -Ofast -CG:cflow=off -LNO:prefetch=1 -OPT:malloc_alg=1

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-exceptions

447.dealIII: -Ofast -INLINE:aggressive=on -LNO:opt=0 -OPT:alias=disjoint
-m32 -fno-exceptions

450.soplex: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:IEEE_arith=3 -CG:load_exe=0 -CG:movnti=1
-LNO:minvariant=off -LNO:prefetch=1 -fno-exceptions

453.povray: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-fast-math

Fortran benchmarks:

410.bwaves: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:Ofast -OPT:IEEE_arith=3 -LNO:blocking=off
-LNO:ignore_feedback=off

416.gamess: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O2
-OPT:Ofast -OPT:ro=3 -OPT:unroll_size=256

434.zeusmp: -Ofast -CG:local_fwd_sched=on -LNO:blocking=off
-LNO:interchange=off -LNO:fu=10 -LNO:full_unroll_outer=on

437.leslie3d: basepeak = yes

459.GemsFDTD: -Ofast -LNO:fission=2 -LNO:prefetch=0

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: -O3 -OPT:rsqrt=2 -OPT:ro=3

436.cactusADM: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-LNO:prefetch=3 -LNO:prefetch_ahead=5 -LNO:ou_prod_max=10
-LNO:full_unroll=5 -ipa

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

IBM Corporation SPECfp2006 = 10.9

IBM System x3655 (AMD Opteron 2212) SPECfp_base2006 = 10.4

CPU2006 license: 11	Test date: Jul-2007
Test sponsor: IBM Corporation	Hardware Availability: Oct-2006
Tested by: IBM Corporation	Software Availability: Mar-2007

Peak Optimization Flags (Continued)

454.calculix: -Ofast -LNO:simd=0 -WOPT:mem_opnds=on
 481.wrf: basepeak = yes

Peak Other Flags

C benchmarks:
-IPA:max_jobs=2

C++ benchmarks:
-IPA:max_jobs=2

Fortran benchmarks:
-IPA:max_jobs=2

Benchmarks using both Fortran and C:
-IPA:max_jobs=2

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.13.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Sep 13 11:24:55 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 August 2007.