



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor E5335,
2.0 GHz

SPECint®_rate2006 = 73.6

SPECint_rate_base2006 = 68.2

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2007

Hardware Availability: Feb-2007

Software Availability: Jun-2007



Hardware

CPU Name: Intel Xeon E5335
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (4x2 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
 Disk Subsystem: Seagate ST336754SS (SAS, 36GB, 15000rpm)
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smpt
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 10.0 - Build 20070308, Package-ID: I_cc_p_10.0.023
 Auto Parallel: No
 File System: ext2
 System State: Multiuser, Runlevel 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Smart Heap Library, Version 8.1
 binutils-2.17.tar.gz, Version 2.17



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor E5335,
2.0 GHz

SPECint_rate2006 = 73.6

SPECint_rate_base2006 = 68.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2007

Hardware Availability: Feb-2007

Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	772	101	<u>767</u>	<u>102</u>	766	102	8	<u>651</u>	<u>120</u>	652	120	648	121
401.bzip2	8	1397	55.3	<u>1390</u>	<u>55.5</u>	1378	56.0	8	1316	58.7	1305	59.2	<u>1306</u>	<u>59.1</u>
403.gcc	8	968	66.5	<u>956</u>	<u>67.3</u>	954	67.5	8	968	66.5	<u>956</u>	<u>67.3</u>	954	67.5
429.mcf	8	1489	49.0	<u>1423</u>	<u>51.3</u>	1419	51.4	8	1332	54.8	<u>1331</u>	<u>54.8</u>	1329	54.9
445.gobmk	8	855	98.1	849	98.9	<u>850</u>	<u>98.8</u>	8	787	107	785	107	<u>786</u>	<u>107</u>
456.hmmmer	8	948	78.7	949	78.6	<u>949</u>	<u>78.7</u>	8	<u>781</u>	<u>95.5</u>	780	95.7	784	95.2
458.sjeng	8	<u>1039</u>	<u>93.2</u>	1037	93.3	1039	93.1	8	928	104	<u>926</u>	<u>104</u>	926	105
462.libquantum	8	7074	23.4	<u>6940</u>	<u>23.9</u>	6916	24.0	8	6069	27.3	6056	27.4	<u>6060</u>	<u>27.4</u>
464.h264ref	8	1110	159	1112	159	<u>1110</u>	<u>159</u>	8	1056	168	1052	168	<u>1054</u>	<u>168</u>
471.omnetpp	8	1155	43.3	<u>1116</u>	<u>44.8</u>	1108	45.1	8	1088	46.0	<u>1087</u>	<u>46.0</u>	1087	46.0
473.astar	8	1163	48.3	1150	48.8	<u>1152</u>	<u>48.7</u>	8	<u>1137</u>	<u>49.4</u>	1128	49.8	1138	49.3
483.xalancbmk	8	649	85.1	636	86.8	<u>639</u>	<u>86.4</u>	8	649	85.1	636	86.8	<u>639</u>	<u>86.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hmmmer in peak were built with 64-bit Intel
compiler by changing the path for include and library files.

BIOS configuration:

Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor E5335,
2.0 GHz

SPECint_rate2006 = 73.6

SPECint_rate_base2006 = 68.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2007

Hardware Availability: Feb-2007

Software Availability: Jun-2007

Base Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-xT -O3 -ipo -no-prec-div -ansi-alias

-L/opt/SmartHeap_8_1/lib -lsmarheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-I/opt/intel/cce/10.0.023/include
-L/opt/intel/cce/10.0.023/lib

456.hmmer: /opt/intel/cce/10.0.023/bin/icc
-I/opt/intel/cce/10.0.023/include
-L/opt/intel/cce/10.0.023/lib

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

401.bzip2: -DSPEC_CPU_LP64

456.hmmer: -DSPEC_CPU_LP64

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor E5335,
2.0 GHz

SPECint_rate2006 = 73.6

SPECint_rate_base2006 = 68.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2007

Hardware Availability: Feb-2007

Software Availability: Jun-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast -prefetch
-L/opt/SmartHeap_8_1/lib -lsmarheap

445.gobmk: Same as 400.perlbench

456.hmmer: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll2

458.sjeng: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll4

462.libquantum: -prof_gen(pass 1) -prof_use(pass 2) -fast -prefetch
-opt-streaming-stores always

464.h264ref: -prof_gen(pass 1) -prof_use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -fast -ansi-alias
-L/opt/SmartHeap_8_1/lib -lsmarheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/FSC_Intel_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/FSC_Intel_flags.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor E5335,
2.0 GHz

SPECint_rate2006 = 73.6

SPECint_rate_base2006 = 68.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2007

Hardware Availability: Feb-2007

Software Availability: Jun-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:30:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 August 2007.