



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint®_rate2006 = 32.7

Acer Altos R520 (Intel Xeon 5160)

SPECint_rate_base2006 = 30.5

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Aug-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007



Hardware

CPU Name: Intel Xeon 5160
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
 Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 EM64T kernel
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.0
 Build 20070426 Package ID: l_cc_p_10.0.023
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.7

Acer Altos R520 (Intel Xeon 5160)

SPECint_rate_base2006 = 30.5

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Aug-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	511	38.2	<u>507</u>	<u>38.5</u>	505	38.7	2	426	45.9	431	45.3	<u>431</u>	<u>45.3</u>
401.bzip2	2	859	22.5	<u>858</u>	<u>22.5</u>	856	22.6	2	808	23.9	<u>809</u>	<u>23.9</u>	813	23.7
403.gcc	2	<u>595</u>	<u>27.1</u>	602	26.7	592	27.2	2	<u>595</u>	<u>27.1</u>	602	26.7	592	27.2
429.mcf	2	648	28.2	<u>648</u>	<u>28.2</u>	647	28.2	2	<u>665</u>	<u>27.4</u>	665	27.4	663	27.5
445.gobmk	2	<u>562</u>	<u>37.3</u>	563	37.3	562	37.3	2	<u>512</u>	<u>41.0</u>	512	41.0	512	41.0
456.hammer	2	<u>597</u>	<u>31.3</u>	597	31.3	597	31.3	2	473	39.4	<u>473</u>	<u>39.5</u>	471	39.6
458.sjeng	2	732	33.1	723	33.5	<u>724</u>	<u>33.4</u>	2	649	37.3	<u>647</u>	<u>37.4</u>	646	37.5
462.libquantum	2	1580	26.2	<u>1584</u>	<u>26.2</u>	1586	26.1	2	1504	27.6	<u>1503</u>	<u>27.6</u>	1502	27.6
464.h264ref	2	742	59.7	744	59.5	<u>742</u>	<u>59.6</u>	2	702	63.0	705	62.8	<u>702</u>	<u>63.0</u>
471.omnetpp	2	660	18.9	661	18.9	<u>660</u>	<u>18.9</u>	2	<u>634</u>	<u>19.7</u>	634	19.7	633	19.7
473.astar	2	634	22.2	<u>632</u>	<u>22.2</u>	631	22.2	2	<u>604</u>	<u>23.2</u>	603	23.3	604	23.2
483.xalancbmk	2	360	38.4	361	38.2	<u>360</u>	<u>38.3</u>	2	360	38.4	361	38.2	<u>360</u>	<u>38.3</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520
The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings

Snoop Filter set to OFF

Snoop Filter preserves cache coherency while minimizing snoops to remote nodes.

Adjacent Cache Line Prefetch set to OFF

Prefetch data in order to shorten execution cycles and maximize data processing efficiency.

Optimization for high-frequency FSB applications set to ON

taskset was used to bind copies to cores

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.7

Acer Altos R520 (Intel Xeon 5160)

SPECint_rate_base2006 = 30.5

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Aug-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

456.hmmer: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.7

Acer Altos R520 (Intel Xeon 5160)

SPECint_rate_base2006 = 30.5

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Aug-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast

403.gcc: basepeak = yes

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec_div -ansi-alias

456.hmmer: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -Ob0
-prefetch -opt-streaming-stores always

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec_div -ansi-alias -Wl,-z,muldefs
-L/spec/cpu2006.1.0/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.7

Acer Altos R520 (Intel Xeon 5160)

SPECint_rate_base2006 = 30.5

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Aug-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:56:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.