



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems
Sun Fire X4450**

**SPECfp®2006 = 21.7
SPECfp_base2006 = 18.9**

CPU2006 license: 6


Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X7350
CPU Characteristics: Quad Core, 2.93 GHz
CPU MHz: 2933
FPU: Integrated
CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip
CPU(s) orderable: 2,4 (order by number of chips)
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1 for x86_64
Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070824
Auto Parallel: Yes
File System: ReiserFS
System State: Multi-user, run level 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems
Sun Fire X4450**

**SPECfp2006 = 21.7
SPECfp_base2006 = 18.9**

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2GB DDR2 PC2-5300F 2rank
CAS 5-5-5 with ECC)
Disk Subsystem: SAS, 73 GB, 10K RPM
Other Hardware: None

Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	313	43.4	<u>313</u>	<u>43.4</u>	315	43.2	312	43.5	309	44.0	<u>310</u>	<u>43.8</u>
416.gamess	985	19.9	<u>989</u>	<u>19.8</u>	990	19.8	<u>925</u>	<u>21.2</u>	924	21.2	925	21.2
433.milc	1062	8.64	1064	8.63	<u>1062</u>	<u>8.64</u>	1044	8.79	<u>1043</u>	<u>8.80</u>	1042	8.81
434.zeusmp	<u>586</u>	<u>15.5</u>	586	15.5	587	15.5	<u>586</u>	<u>15.5</u>	586	15.5	587	15.5
435.gromacs	385	18.5	<u>385</u>	<u>18.5</u>	386	18.5	385	18.5	<u>385</u>	<u>18.5</u>	386	18.5
436.cactusADM	282	42.4	<u>282</u>	<u>42.4</u>	283	42.2	77.6	154	77.8	154	<u>77.7</u>	<u>154</u>
437.leslie3d	647	14.5	<u>649</u>	<u>14.5</u>	652	14.4	647	14.5	<u>649</u>	<u>14.5</u>	652	14.4
444.namd	<u>515</u>	<u>15.6</u>	515	15.6	516	15.5	<u>512</u>	<u>15.7</u>	<u>512</u>	<u>15.7</u>	<u>512</u>	<u>15.7</u>
447.dealII	429	26.7	<u>429</u>	<u>26.7</u>	429	26.7	409	28.0	<u>408</u>	<u>28.0</u>	408	28.1
450.soplex	680	12.3	684	12.2	<u>682</u>	<u>12.2</u>	624	13.4	<u>625</u>	<u>13.3</u>	625	13.3
453.povray	223	23.9	<u>224</u>	<u>23.8</u>	227	23.4	192	27.7	192	27.7	<u>192</u>	<u>27.7</u>
454.calculix	552	15.0	552	14.9	<u>552</u>	<u>14.9</u>	376	21.9	378	21.8	<u>377</u>	<u>21.9</u>
459.GemsFDTD	491	21.6	<u>491</u>	<u>21.6</u>	492	21.6	480	22.1	479	22.2	<u>479</u>	<u>22.2</u>
465.tonto	525	18.8	<u>524</u>	<u>18.8</u>	495	19.9	<u>474</u>	<u>20.8</u>	<u>474</u>	<u>20.8</u>	475	20.7
470.lbm	1132	12.1	<u>1130</u>	<u>12.2</u>	1122	12.3	956	14.4	<u>956</u>	<u>14.4</u>	954	14.4
481.wrf	568	19.6	568	19.7	<u>568</u>	<u>19.7</u>	568	19.6	568	19.7	<u>568</u>	<u>19.7</u>
482.sphinx3	<u>916</u>	<u>21.3</u>	926	21.1	907	21.5	877	22.2	<u>877</u>	<u>22.2</u>	872	22.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited
OMP_NUM_THREADS set to 16
KMP_STACKSIZE set to 200M
KMP_AFFINITY set to physical,0

Platform Notes

Default BIOS configuration was used.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4450

SPECfp2006 = 21.7
SPECfp_base2006 = 18.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

General Notes

All benchmarks were compiled in 64-bit mode except 450.soplex, 470.lbm and 482.sphinx3 for peak were compiled in 32-bit mode

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast -parallel

C++ benchmarks:

-fast -parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems
Sun Fire X4450**

**SPECfp2006 = 21.7
SPECfp_base2006 = 18.9**

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast -parallel

Benchmarks using both Fortran and C:

-fast -parallel

Peak Compiler Invocation

C benchmarks (except as noted below):

/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/bin/icpc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux32/include

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4450

SPECfp2006 = 21.7
SPECfp_base2006 = 18.9

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4450

SPECfp2006 = 21.7
SPECfp_base2006 = 18.9

CPU2006 license: 6

Test date: Oct-2007

Test sponsor: Sun Microsystems

Hardware Availability: Nov-2007

Tested by: Sun Microsystems

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.22.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.22.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 14:16:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 30 October 2007.