



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 84.7

IBM BladeCenter JS22 (4.0 GHz, 4 core, SLES)

SPECint_rate_base2006 = 77.2

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Oct-2007

Hardware Availability: Nov-2007

Software Availability: Sep-2007



Hardware

CPU Name: POWER6
CPU Characteristics:
CPU MHz: 4000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable: 4 cores
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per core
L3 Cache: None
Other Cache: None
Memory: 16 GB (4x4 GB) DDR2 667 MHz
Disk Subsystem: 1x73 GB SAS 15K RPM
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise 10 SP1
Compiler: IBM XL C/C++ Advanced Edition for Linux, V9.0
Auto Parallel: No
File System: ext3
System State: Multi-User
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: -IBM Post-Link Optimization for Linux on POWER, Version 5.4.0-10
-MicroQuill SmartHeap 7.3



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 84.7

IBM BladeCenter JS22 (4.0 GHz, 4 core, SLES)

SPECint_rate_base2006 = 77.2

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Nov-2007

Tested by: IBM Corporation

Software Availability: Sep-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	1306	59.8	<u>1304</u>	<u>59.9</u>	1304	59.9	8	1058	73.9	<u>1057</u>	<u>74.0</u>	1052	74.3
401.bzip2	8	1068	72.3	1118	69.0	<u>1080</u>	<u>71.5</u>	8	<u>974</u>	<u>79.3</u>	988	78.2	971	79.5
403.gcc	8	883	72.9	880	73.2	<u>881</u>	<u>73.1</u>	8	834	77.2	832	77.4	<u>832</u>	<u>77.4</u>
429.mcf	8	<u>581</u>	<u>126</u>	581	126	581	126	8	<u>580</u>	<u>126</u>	579	126	580	126
445.gobmk	8	1009	83.2	<u>1007</u>	<u>83.3</u>	1006	83.5	8	890	94.3	886	94.8	<u>887</u>	<u>94.6</u>
456.hammer	8	<u>982</u>	<u>76.0</u>	982	76.0	982	76.0	8	908	82.2	907	82.3	<u>907</u>	<u>82.3</u>
458.sjeng	8	1282	75.5	<u>1281</u>	<u>75.6</u>	1279	75.7	8	1163	83.2	1163	83.2	<u>1163</u>	<u>83.2</u>
462.libquantum	8	1309	127	1307	127	<u>1308</u>	<u>127</u>	8	<u>1296</u>	<u>128</u>	1299	128	1296	128
464.h264ref	8	1430	124	<u>1431</u>	<u>124</u>	1431	124	8	1195	148	1186	149	<u>1187</u>	<u>149</u>
471.omnetpp	8	1269	39.4	1268	39.4	<u>1269</u>	<u>39.4</u>	8	1229	40.7	<u>1231</u>	<u>40.6</u>	1232	40.6
473.astar	8	1102	51.0	<u>1103</u>	<u>50.9</u>	1105	50.8	8	964	58.2	970	57.9	<u>967</u>	<u>58.1</u>
483.xalancbmk	8	728	75.8	729	75.7	<u>729</u>	<u>75.8</u>	8	<u>678</u>	<u>81.4</u>	679	81.2	678	81.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

kernel release 2.6.16.53-0.8-ppc64.

See flags file for details on following settings.

ulimit -s (stack) set to unlimited.

The binaries were compiled on a system with 32 GB of memory.

Large pages reserved as follows by root user:

```
echo 530 > /proc/sys/vm/nr_hugepages
```

System configured with libhugetlbfs library for application access to large pages
Environment variables set before executing benchmarks.

```
export HUGETLB_VERBOSE=0
export HUGETLB_MORECORE=yes
export HUGETLB_MORECORE_HEAPBASE=0x50000000
export XLF RTEOPTS=intrinthds=1
```

fdpr binary optimization tool used for
400.perlbench 401.bzip2 403.gcc 429.mcf 456.hammer 458.sjeng
462.libquantum 464.h264ref 473.astar 483.xalancbmk

Benchmarks bound to a processor using numactl on the submit command.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 84.7

IBM BladeCenter JS22 (4.0 GHz, 4 core, SLES)

SPECint_rate_base2006 = 77.2

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Nov-2007

Tested by: IBM Corporation

Software Availability: Sep-2007

Base Compiler Invocation

C benchmarks:

`xlc -qlanglvl=extc99`

C++ benchmarks:

`x1C`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_PPC`

462.libquantum: `-DSPEC_CPU_LINUX`

464.h264ref: `-qchars=signed`

483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:

`-O5 -qalias=noansi -galloca -lhugetlbfs`

C++ benchmarks:

`-O5 -qrtti -lsmartheap`

Base Other Flags

C benchmarks:

`-qipa=noobject -qipa=threads`

C++ benchmarks:

`-qipa=noobject -qipa=threads`

Peak Compiler Invocation

C benchmarks:

`xlc -qlanglvl=extc99`

C++ benchmarks:

`x1C`



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 84.7

IBM BladeCenter JS22 (4.0 GHz, 4 core, SLES)

SPECint_rate_base2006 = 77.2

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Nov-2007

Tested by: IBM Corporation

Software Availability: Sep-2007

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_PPC
    403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
    464.h264ref: -qchars=signed
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalias=noansi
    -lsmartheap

401.bzip2: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -lhugetlbfs

403.gcc: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalloc -q64
    -lhugetlbfs

429.mcf: -Wl,-q -O5 -qnoenablevmx -lhugetlbfs

445.gobmk: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qnoenablevmx
    -lhugetlbfs

456.hmmer: Same as 401.bzip2

458.sjeng: Same as 401.bzip2

462.libquantum: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx
    -q64 -lhugetlbfs

464.h264ref: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -q64
    -lhugetlbfs
```

C++ benchmarks:

```
471.omnetpp: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qrtti -lsmartheap

473.astar: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx
    -lsmartheap

483.xalancbmk: -Wl,-q -O4 -lsmartheap
```

Peak Other Flags

C benchmarks:

-qipa=noobject -qipa=threads

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = 84.7

IBM BladeCenter JS22 (4.0 GHz, 4 core, SLES)

SPECint_rate_base2006 = 77.2

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Nov-2007

Tested by: IBM Corporation

Software Availability: Sep-2007

Peak Other Flags (Continued)

C++ benchmarks:

-qipa=noobject -qipa=threads

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 14:26:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 27 November 2007.