



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint®_rate2006 = 27.2

Acer Altos R520 (Intel Xeon 5130)

SPECint_rate_base2006 = 24.0

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007



SPECint_rate_base2006 = 24.0

SPECint_rate2006 = 27.2

Hardware

CPU Name: Intel Xeon 5130
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
 Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 27.2

Acer Altos R520 (Intel Xeon 5130)

SPECint_rate_base2006 = 24.0

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	730	26.8	732	26.7	<u>731</u>	<u>26.7</u>	2	623	31.3	626	31.2	<u>625</u>	<u>31.3</u>
401.bzip2	2	1145	16.9	1153	16.7	<u>1151</u>	<u>16.8</u>	2	1078	17.9	1085	17.8	<u>1084</u>	<u>17.8</u>
403.gcc	2	<u>680</u>	<u>23.7</u>	677	23.8	685	23.5	2	688	23.4	<u>675</u>	<u>23.8</u>	673	23.9
429.mcf	2	752	24.2	<u>752</u>	<u>24.3</u>	749	24.3	2	709	25.7	711	25.7	<u>711</u>	<u>25.7</u>
445.gobmk	2	803	26.1	<u>803</u>	<u>26.1</u>	803	26.1	2	737	28.5	735	28.5	<u>736</u>	<u>28.5</u>
456.hammer	2	888	21.0	<u>888</u>	<u>21.0</u>	889	21.0	2	<u>519</u>	<u>36.0</u>	518	36.0	519	35.9
458.sjeng	2	<u>998</u>	<u>24.2</u>	993	24.4	1001	24.2	2	910	26.6	913	26.5	<u>910</u>	<u>26.6</u>
462.libquantum	2	1538	26.9	1534	27.0	<u>1538</u>	<u>26.9</u>	1	558	37.1	<u>558</u>	<u>37.1</u>	558	37.1
464.h264ref	2	<u>1101</u>	<u>40.2</u>	1102	40.2	1101	40.2	2	<u>1039</u>	<u>42.6</u>	1039	42.6	1040	42.6
471.omnetpp	2	684	18.3	701	17.8	<u>688</u>	<u>18.2</u>	2	635	19.7	634	19.7	<u>634</u>	<u>19.7</u>
473.astar	2	807	17.4	<u>805</u>	<u>17.4</u>	805	17.4	2	741	18.9	<u>742</u>	<u>18.9</u>	743	18.9
483.xalancbmk	2	454	30.4	455	30.4	<u>454</u>	<u>30.4</u>	2	454	30.4	455	30.4	<u>454</u>	<u>30.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings

Hardware Prefetcher set to ON

Adjacent Cache Line Prefetch set to OFF

Optimization for high-frequency FSB applications set to ON

All results used taskset to bind processes to cores.

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 27.2

Acer Altos R520 (Intel Xeon 5130)

SPECint_rate_base2006 = 24.0

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 27.2

Acer Altos R520 (Intel Xeon 5130)

SPECint_rate_base2006 = 24.0

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalanbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalanbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 27.2

Acer Altos R520 (Intel Xeon 5130)

SPECint_rate_base2006 = 24.0

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.22.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.22.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:52:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 December 2007.