



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®2006 = 24.0

IBM System x3500 (Intel Xeon E5430)

SPECint_base2006 = 20.9

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Apr-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5430
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)
 Disk Subsystem: 1 x 80 GB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smp
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 24.0

IBM System x3500 (Intel Xeon E5430)

SPECint_base2006 = 20.9

CPU2006 license: 11

Test date: Apr-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	560	17.4	562	17.4	<u>562</u>	<u>17.4</u>	450	21.7	<u>450</u>	<u>21.7</u>	453	21.6
401.bzip2	<u>665</u>	<u>14.5</u>	665	14.5	669	14.4	<u>616</u>	<u>15.7</u>	615	15.7	616	15.7
403.gcc	597	13.5	594	13.6	<u>594</u>	<u>13.5</u>	<u>445</u>	<u>18.1</u>	444	18.1	445	18.1
429.mcf	443	20.6	<u>443</u>	<u>20.6</u>	443	20.6	<u>410</u>	<u>22.3</u>	410	22.2	409	22.3
445.gobmk	599	17.5	599	17.5	<u>599</u>	<u>17.5</u>	<u>540</u>	<u>19.4</u>	540	19.4	540	19.4
456.hmmer	667	14.0	669	13.9	<u>667</u>	<u>14.0</u>	<u>384</u>	<u>24.3</u>	384	24.3	385	24.2
458.sjeng	<u>759</u>	<u>15.9</u>	758	16.0	763	15.8	<u>684</u>	<u>17.7</u>	682	17.7	685	17.7
462.libquantum	105	196	101	206	<u>102</u>	<u>204</u>	102	202	103	200	<u>103</u>	<u>201</u>
464.h264ref	801	27.6	<u>802</u>	<u>27.6</u>	804	27.5	748	29.6	748	29.6	<u>748</u>	<u>29.6</u>
471.omnetpp	<u>439</u>	<u>14.2</u>	438	14.3	439	14.2	397	15.7	399	15.7	<u>399</u>	<u>15.7</u>
473.astar	519	13.5	525	13.4	<u>521</u>	<u>13.5</u>	<u>472</u>	<u>14.9</u>	472	14.9	472	14.9
483.xalancbmk	297	23.2	298	23.2	<u>298</u>	<u>23.2</u>	297	23.2	298	23.2	<u>298</u>	<u>23.2</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer, for peak, are compiled in 64-bit mode
Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Enabled
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to null
This result is measured on an IBM System x 3500 Server. Note that the IBM System x 3500 and IBM System x 3400 are electrically equivalent.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 24.0

IBM System x3500 (Intel Xeon E5430)

SPECint_base2006 = 20.9

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Apr-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmarheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 24.0

IBM System x3500 (Intel Xeon E5430)

SPECint_base2006 = 20.9

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Apr-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	SPECint2006 =	24.0
IBM System x3500 (Intel Xeon E5430)	SPECint_base2006 =	20.9

CPU2006 license: 11	Test date: Apr-2008
Test sponsor: IBM Corporation	Hardware Availability: Jan-2008
Tested by: IBM Corporation	Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090714.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:12:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 13 May 2008.