



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp[®]_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5430
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64) SP1
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008,
 l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3211	33.9	3213	33.8	<u>3212</u>	<u>33.9</u>	4	<u>1574</u>	<u>34.5</u>	1574	34.5	1574	34.5
416.gamess	8	997	157	998	157	<u>997</u>	<u>157</u>	8	<u>983</u>	<u>159</u>	985	159	983	159
433.milc	8	3421	21.5	3415	21.5	<u>3420</u>	<u>21.5</u>	8	3382	21.7	3369	21.8	<u>3378</u>	<u>21.7</u>
434.zeusmp	8	1025	71.0	1034	70.4	<u>1028</u>	<u>70.8</u>	8	<u>1021</u>	<u>71.3</u>	1017	71.5	1023	71.2
435.gromacs	8	429	133	<u>426</u>	<u>134</u>	424	135	8	418	137	<u>420</u>	<u>136</u>	420	136
436.cactusADM	8	<u>1317</u>	<u>72.6</u>	1318	72.5	1315	72.7	1	<u>125</u>	<u>95.5</u>	124	96.0	126	95.2
437.leslie3d	8	<u>2864</u>	<u>26.3</u>	2871	26.2	2860	26.3	4	1303	28.9	<u>1302</u>	<u>28.9</u>	1302	28.9
444.namd	8	569	113	569	113	<u>569</u>	<u>113</u>	8	<u>566</u>	<u>113</u>	566	113	565	114
447.dealII	8	686	133	<u>680</u>	<u>135</u>	675	136	8	717	128	665	138	<u>667</u>	<u>137</u>
450.soplex	8	1987	33.6	1989	33.5	<u>1988</u>	<u>33.6</u>	8	<u>1786</u>	<u>37.4</u>	1787	37.3	1782	37.4
453.povray	8	238	179	241	177	<u>238</u>	<u>179</u>	8	203	210	203	210	<u>203</u>	<u>210</u>
454.calculix	8	599	110	597	111	<u>597</u>	<u>111</u>	8	430	154	432	153	<u>430</u>	<u>153</u>
459.GemsFDTD	8	3450	24.6	3449	24.6	<u>3449</u>	<u>24.6</u>	8	<u>3349</u>	<u>25.3</u>	3355	25.3	3345	25.4
465.tonto	8	693	114	687	115	<u>692</u>	<u>114</u>	8	674	117	680	116	<u>675</u>	<u>117</u>
470.lbm	8	<u>4212</u>	<u>26.1</u>	4211	26.1	4220	26.0	4	1447	38.0	<u>1447</u>	<u>38.0</u>	1447	38.0
481.wrf	8	1728	51.7	1723	51.9	<u>1728</u>	<u>51.7</u>	8	<u>1725</u>	<u>51.8</u>	1725	51.8	1727	51.7
482.sphinx3	8	2866	54.4	<u>2843</u>	<u>54.8</u>	2836	55.0	4	860	90.6	858	90.9	<u>858</u>	<u>90.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 71.3

SPECfp_rate_base2006 = 63.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -unroll-aggressive -auto-ilp32
481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 18:43:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 30 September 2008.