



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

### SPECfp<sup>®</sup>\_rate2006 = 38.4

### PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

### SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2008

Hardware Availability: Dec-2007

Software Availability: May-2008



#### Hardware

CPU Name: Intel Xeon E5405  
 CPU Characteristics: 1333 MHz system bus  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

#### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) with SP2, kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 Version 10.1 - Build 20070913  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Multi-User Run Level 3  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

SPECfp\_rate2006 = 38.4

PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 22

Test date: Aug-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL 5-5-5, ECC)  
Disk Subsystem: 1x SAS, 73 GB, 15000 rpm  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.50.0.5-0.1.x86\_64

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2312	23.5	<u>2222</u>	<u>24.5</u>	2219	24.5	4	2042	26.6	<u>2032</u>	<u>26.8</u>	2019	26.9
416.gamess	4	1328	59.0	<u>1329</u>	<u>58.9</u>	1329	58.9	4	1314	59.6	1313	59.7	<u>1313</u>	<u>59.6</u>
433.milc	4	1814	20.2	<u>1732</u>	<u>21.2</u>	1731	21.2	4	1704	21.6	<u>1667</u>	<u>22.0</u>	1666	22.0
434.zeusmp	4	<u>950</u>	<u>38.3</u>	950	38.3	937	38.9	4	936	38.9	<u>958</u>	<u>38.0</u>	959	38.0
435.gromacs	4	562	50.9	<u>563</u>	<u>50.7</u>	564	50.7	4	<u>554</u>	<u>51.5</u>	554	51.5	554	51.5
436.cactusADM	4	1076	44.4	1064	44.9	<u>1064</u>	<u>44.9</u>	1	218	54.8	217	55.2	<u>218</u>	<u>54.8</u>
437.leslie3d	4	2293	16.4	<u>2275</u>	<u>16.5</u>	2226	16.9	4	1888	19.9	<u>1880</u>	<u>20.0</u>	1862	20.2
444.namd	4	<u>760</u>	<u>42.2</u>	759	42.3	761	42.1	4	756	42.5	754	42.5	<u>754</u>	<u>42.5</u>
447.dealII	4	753	60.8	744	61.5	<u>748</u>	<u>61.2</u>	4	<u>709</u>	<u>64.6</u>	719	63.6	708	64.7
450.soplex	4	1506	22.2	<u>1467</u>	<u>22.7</u>	1458	22.9	4	1180	28.3	<u>1169</u>	<u>28.5</u>	1163	28.7
453.povray	4	316	67.3	315	67.6	<u>316</u>	<u>67.4</u>	4	268	79.4	269	79.1	<u>268</u>	<u>79.3</u>
454.calculix	4	778	42.4	<u>778</u>	<u>42.4</u>	778	42.4	4	538	61.3	<u>540</u>	<u>61.1</u>	541	61.0
459.GemsFDTD	4	2316	18.3	2278	18.6	<u>2290</u>	<u>18.5</u>	4	2242	18.9	2228	19.0	<u>2234</u>	<u>19.0</u>
465.tonto	4	793	49.6	<u>798</u>	<u>49.3</u>	799	49.3	4	772	51.0	769	51.2	<u>771</u>	<u>51.1</u>
470.lbm	4	3065	17.9	<u>3031</u>	<u>18.1</u>	3025	18.2	2	1022	26.9	<u>1017</u>	<u>27.0</u>	1014	27.1
481.wrf	4	1501	29.8	<u>1490</u>	<u>30.0</u>	1488	30.0	4	1440	31.0	<u>1442</u>	<u>31.0</u>	1446	30.9
482.sphinx3	4	2325	33.5	<u>2417</u>	<u>32.3</u>	2424	32.2	2	<u>1042</u>	<u>37.4</u>	1041	37.5	1058	36.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores (default)

## Platform Notes

BIOS configuration:  
Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable

## General Notes

For information about Fujitsu Siemens Computers please see:  
<http://www.fujitsu-siemens.com>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp\_rate2006 = 38.4

PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2008

Hardware Availability: Dec-2007

Software Availability: May-2008

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp\_rate2006 = 38.4

PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 22

Test date: Aug-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp\_rate2006 = 38.4

PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Aug-2008

Hardware Availability: Dec-2007

Software Availability: May-2008

## Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECfp\_rate2006 = 38.4

PRIMERGY RX300 S4, Intel Xeon E5405, 2.0 GHz

SPECfp\_rate\_base2006 = 34.2

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Aug-2008

**Hardware Availability:** Dec-2007

**Software Availability:** May-2008

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags-ic101-linux-intel64.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 22:19:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 14 October 2008.