



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECint®\_rate2006 = 783

Express5800/A1080a-S (Intel Xeon E7-8830)

SPECint\_rate\_base2006 = 737

CPU2006 license: 9006


Test date: Aug-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011



SPECint\_rate2006 = 783

SPECint\_rate\_base2006 = 737

### Hardware

CPU Name: Intel Xeon E7-8830  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.40 GHz  
 CPU MHz: 2133  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2,3,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 24 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (64 x 4 GB 2Rx4 PC3-8500R-7, ECC)  
 Disk Subsystem: 2x300 GB SAS, 10000 RPM, RAID 0  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.1, Kernel 2.6.32-131.0.15.el6.x86\_64 on an x86\_64  
 Compiler: C/C++: Version 12.0.4.191 of Intel Compiler XE for applications on IA-32 Build 20110427  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V9.01



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECint\_rate2006 = 783

Express5800/A1080a-S (Intel Xeon E7-8830)

SPECint\_rate\_base2006 = 737

CPU2006 license: 9006

Test date: Aug-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	64	<b><u>1085</u></b>	<b><u>576</u></b>	1083	577	1089	574	64	<b><u>906</u></b>	<b><u>690</u></b>	906	690	904	692
401.bzip2	64	1462	423	1464	422	<b><u>1462</u></b>	<b><u>423</u></b>	64	1373	450	<b><u>1373</u></b>	<b><u>450</u></b>	1376	449
403.gcc	64	<b><u>839</u></b>	<b><u>614</u></b>	839	614	841	613	64	<b><u>842</u></b>	<b><u>612</u></b>	846	609	837	615
429.mcf	64	585	998	586	997	<b><u>585</u></b>	<b><u>998</u></b>	64	589	991	<b><u>589</u></b>	<b><u>992</u></b>	587	994
445.gobmk	64	1033	650	1037	648	<b><u>1037</u></b>	<b><u>648</u></b>	64	941	713	<b><u>939</u></b>	<b><u>715</u></b>	939	715
456.hammer	64	<b><u>656</u></b>	<b><u>910</u></b>	658	907	656	910	64	<b><u>506</u></b>	<b><u>1180</u></b>	506	1180	506	1180
458.sjeng	64	<b><u>1244</u></b>	<b><u>623</u></b>	1244	623	1244	622	64	1162	667	1158	669	<b><u>1160</u></b>	<b><u>668</u></b>
462.libquantum	64	387	3430	387	3430	<b><u>387</u></b>	<b><u>3430</u></b>	64	387	3430	387	3430	<b><u>387</u></b>	<b><u>3430</u></b>
464.h264ref	64	1567	904	1553	912	<b><u>1564</u></b>	<b><u>906</u></b>	64	1610	880	1572	901	<b><u>1601</u></b>	<b><u>885</u></b>
471.omnetpp	64	<b><u>879</u></b>	<b><u>455</u></b>	879	455	880	455	64	810	494	<b><u>810</u></b>	<b><u>494</u></b>	811	493
473.astar	64	<b><u>996</u></b>	<b><u>451</u></b>	994	452	999	450	64	<b><u>996</u></b>	<b><u>451</u></b>	994	452	999	450
483.xalancbmk	64	595	743	<b><u>595</u></b>	<b><u>743</u></b>	595	742	64	595	743	<b><u>595</u></b>	<b><u>743</u></b>	595	742

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run  
echo 1 > /proc/sys/vm/zone\_reclaim\_mode  
Huge pages were not configured for this run

## Platform Notes

Patrol Scrubbing set to disabled in Maintenance Console

## General Notes

The Express5800/A1080a-S and the Express5800/A1080a-D models are electronically equivalent.  
The results have been measured on the Express5800/A1080a-S model.  
Binaries were compiled on RHEL 5.6

## Base Compiler Invocation

C benchmarks:  
icc -m32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 783

Express5800/A1080a-S (Intel Xeon E7-8830)

SPECint\_rate\_base2006 = 737

CPU2006 license: 9006

Test date: Aug-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch  
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

C++ benchmarks:  
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/opt/SmartHeap\_9/lib -lsmartheap  
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc -m32

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:  
icpc -m32



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 783

Express5800/A1080a-S (Intel Xeon E7-8830)

SPECint\_rate\_base2006 = 737

CPU2006 license: 9006

Test date: Aug-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
 401.bzip2: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LINUX  
 483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -ansi-alias

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div  
 -B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

429.mcf: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -ansi-alias -auto-ilp32

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
 -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32  
 -B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -unroll4 -auto-ilp32  
 -B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
 -L/opt/SmartHeap\_9/lib -lsmartheap

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 783

Express5800/A1080a-S (Intel Xeon E7-8830)

SPECint\_rate\_base2006 = 737

CPU2006 license: 9006

Test date: Aug-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011

## Peak Optimization Flags (Continued)

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110705.html>

<http://www.spec.org/cpu2006/flags/NEC-platform-linux64-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110705.xml>

<http://www.spec.org/cpu2006/flags/NEC-platform-linux64-revB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Thu Jul 24 01:50:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 25 October 2011.