



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp<sup>®</sup>2006 = **92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

SPECfp\_base2006 = **88.4**

CPU2006 license: 19


Test date: Sep-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013



Hardware	
CPU Name:	Intel Xeon E5-2660 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.00 GHz
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	20 cores, 2 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software	
Operating System:	Red Hat Enterprise Linux Server release 6.4 (Santiago) 2.6.32-358.11.1.el6.x86_64
Compiler:	C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux; Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
Auto Parallel:	Yes
File System:	ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

SPECfp\_base2006 = **88.4**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Sep-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013

L3 Cache: 25 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC3-14900R-13, ECC)  
 Disk Subsystem: 1 x SATA, 450 GB, 15000 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	29.8	456	29.4	462	<b><u>29.6</u></b>	<b><u>459</u></b>	29.8	456	29.4	462	<b><u>29.6</u></b>	<b><u>459</u></b>
416.gamess	712	27.5	713	27.5	<b><u>712</u></b>	<b><u>27.5</u></b>	604	32.4	602	32.5	<b><u>603</u></b>	<b><u>32.5</u></b>
433.milc	<b><u>148</u></b>	<b><u>61.9</u></b>	148	62.2	148	61.9	145	63.2	<b><u>146</u></b>	<b><u>63.1</u></b>	146	63.0
434.zeusmp	58.8	155	59.0	154	<b><u>58.8</u></b>	<b><u>155</u></b>	58.8	155	59.0	154	<b><u>58.8</u></b>	<b><u>155</u></b>
435.gromacs	197	36.3	<b><u>197</u></b>	<b><u>36.3</u></b>	197	36.2	197	36.3	<b><u>197</u></b>	<b><u>36.3</u></b>	197	36.2
436.cactusADM	19.3	620	19.7	607	<b><u>19.7</u></b>	<b><u>607</u></b>	19.3	620	19.7	607	<b><u>19.7</u></b>	<b><u>607</u></b>
437.leslie3d	<b><u>30.2</u></b>	<b><u>311</u></b>	35.2	267	29.8	315	<b><u>30.2</u></b>	<b><u>311</u></b>	35.2	267	29.8	315
444.namd	388	20.6	388	20.7	<b><u>388</u></b>	<b><u>20.7</u></b>	<b><u>380</u></b>	<b><u>21.1</u></b>	380	21.1	380	21.1
447.dealII	237	48.4	<b><u>237</u></b>	<b><u>48.4</u></b>	237	48.3	237	48.4	<b><u>237</u></b>	<b><u>48.4</u></b>	237	48.3
450.soplex	199	41.9	<b><u>199</u></b>	<b><u>41.9</u></b>	200	41.8	199	41.9	<b><u>199</u></b>	<b><u>41.9</u></b>	200	41.8
453.povray	132	40.2	133	40.1	<b><u>133</u></b>	<b><u>40.1</u></b>	112	47.3	<b><u>112</u></b>	<b><u>47.4</u></b>	112	47.6
454.calculix	207	39.8	<b><u>207</u></b>	<b><u>39.9</u></b>	206	40.0	<b><u>192</u></b>	<b><u>43.0</u></b>	192	43.0	192	43.0
459.GemsFDTD	55.1	193	55.3	192	<b><u>55.1</u></b>	<b><u>193</u></b>	50.3	211	<b><u>49.7</u></b>	<b><u>213</u></b>	49.5	214
465.tonto	307	32.0	<b><u>304</u></b>	<b><u>32.3</u></b>	304	32.4	<b><u>242</u></b>	<b><u>40.7</u></b>	242	40.6	241	40.8
470.lbm	22.8	602	23.4	587	<b><u>23.0</u></b>	<b><u>597</u></b>	22.8	602	23.4	587	<b><u>23.0</u></b>	<b><u>597</u></b>
481.wrf	119	94.0	120	93.2	<b><u>119</u></b>	<b><u>93.8</u></b>	119	94.0	120	93.2	<b><u>119</u></b>	<b><u>93.8</u></b>
482.sphinx3	<b><u>304</u></b>	<b><u>64.0</u></b>	305	64.0	304	64.1	<b><u>304</u></b>	<b><u>64.0</u></b>	305	64.0	304	64.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Energy Performance = Performance  
 Utilization Profile = Unbalanced

## General Notes

Environment variables set by runspec before the start of the run:  
 KMP\_AFFINITY = "granularity=fine,compact,1,0"  
 LD\_LIBRARY\_PATH = "/SPECcpu2006/libs/32:/SPECcpu2006/libs/64:/SPECcpu2006/sh"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

**SPECfp2006 = 92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

**SPECfp\_base2006 = 88.4**

**CPU2006 license:** 19

**Test date:** Sep-2013

**Test sponsor:** Fujitsu

**Hardware Availability:** Oct-2013

**Tested by:** Fujitsu

**Software Availability:** Sep-2013

## General Notes (Continued)

OMP\_NUM\_THREADS = "20"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

This result was measured on the PRIMERGY RX350 S8. The PRIMERGY RX350 S8 and the PRIMERGY TX300 S8 are electronically equivalent.

For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

**SPECfp\_base2006 = 88.4**

**CPU2006 license:** 19  
**Test sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test date:** Sep-2013  
**Hardware Availability:** Oct-2013  
**Software Availability:** Sep-2013

## Base Optimization Flags

C benchmarks:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

C++ benchmarks:  
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:  
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

## Peak Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32  
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

**SPECfp\_base2006 = 88.4**

CPU2006 license: 19

Test date: Sep-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013

## Peak Optimization Flags (Continued)

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20130924.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20130924.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

**SPECfp2006 = 92.6**

PRIMERGY TX300 S8, Intel Xeon E5-2660 v2, 2.20 GHz

**SPECfp\_base2006 = 88.4**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Sep-2013

**Hardware Availability:** Oct-2013

**Software Availability:** Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 17:32:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 November 2013.