



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp[®]_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Apr-2014

Hardware Availability: Jun-2014

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

	Copies
410.bwaves	
416.gamess	
433.milc	
434.zeusmp	
435.gromacs	
436.cactusADM	
437.leslie3d	
444.namd	
447.dealII	
450.soplex	
453.povray	
454.calculix	
459.G	
465.tonto	
470.lbm	
481.wrf	
482.sphinx3	

Non-Compliant



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Apr-2014
Hardware Availability: Jun-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Hardware

CPU Name: Intel Xeon E7-4830 v2
CPU Characteristics: Intel Turbo Boost Technology up to 2.70 GHz
CPU MHz: 2200
FPU: Integrated
CPU(s) enabled: 40 cores, 4 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable: 4 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core
L3 Cache: 20 MB I+D on chip per chip
Other Cache: None
Memory: 1 TB (64 x 16 GB 2Rx4 PCBL-12800R-11, ECC, running at 1333 MHz and CL9)
Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
Compiler: 2.6.32-431.el6.x86_64
C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
Arch Parallel: No
File System: ext4
System State: Run level 5 (multi-user)
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: None

Non-Compliant



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Apr-2014
Hardware Availability: Jun-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
416.gamess	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
433.milc	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
434.zeusmp	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
435.gromacs	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
436.cactusADM	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
437.leslie3d	80	NC	NC	NC	NC	NC	NC	40	NC	NC	NC	NC	NC	NC		
444.namd	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
447.dealII	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
450.soplex	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
453.povray	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
454.calculix	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
459.GemsFDTD	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
465.tonto	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
470.lbm	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
481.wrf	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		
482.sphinx3	80	NC	NC	NC	NC	NC	NC	80	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Apr-2014

Hardware Availability: Jun-2014

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Platform Notes

BIOS configuration:
Energy Performance = Performance

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/SPECcpu2006/libs/64:/SPECcpu2006/libs/64:/SPECcpu2006/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>
For information about Fujitsu please visit: <http://www.fujitsu.com>

Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Apr-2014
Hardware Availability: Jun-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Base Portability Flags (Continued)

```

416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

```

C benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

C++ benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

Fortran benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Apr-2014
Hardware Availability: Jun-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

423.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-fno-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -auto-ilp32

470.tomriddle: basepeak = yes

472.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealIII: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Apr-2014
Hardware Availability: Jun-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

Peak Optimization Flags (Continued)

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12
-inline-level=0 -salar-sep-

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.cactusADM: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX4770 M1, Intel Xeon E7-4830 v2, 2.20 GHz

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Apr-2014

Hardware Availability: Jun-2014

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Fujitsu or Intel.

The flags files that were used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-evB.html>
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20131009.html>

You can also download the XML flags source by saving the following links:
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-evB.xml>
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20131009.xml>

Non-Compliant

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Sep 19 15:53:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 June 2014.