



# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp®2006 = NC

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = NC

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

- 410.bwaves |
- 416.gamess |
- 433.milc |
- 434.zeusmp |
- 435.gromacs |
- 436.cactusADM |
- 437.leslie3d |
- 444.namd |
- 447.dealII |
- 450.soplex |
- 453.povray |
- 454.calculix |
- 459.GemsFDTD |
- 465.tonto |
- 471.lbm |
- 481.wrf |
- 482.sphinx3 |

**Non-Compliant**



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = **NC**

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = **NC**

CPU2006 license: 3175

Test date: Feb-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

### Hardware

CPU Name: Intel Xeon E5-2630 v4  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.10 GHz  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 25 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2400R, running at 2133 MHz)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
 3.10.0-123.el7.x86\_64  
 Compiler: C/C++ version 16.0.0.101 of Intel C++ Studio XE for Linux;  
 Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux  
 Architecture: Parallel Yes  
 File System: xfs  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

**Non-Compliant**



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = NC

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = NC

CPU2006 license: 3175

Test date: Feb-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Results Table

| Benchmark     | Base    |       |         |       |         |       | Peak    |       |         |       |         |       |
|---------------|---------|-------|---------|-------|---------|-------|---------|-------|---------|-------|---------|-------|
|               | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 416.gamess    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 433.milc      | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 434.zeusmp    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 435.gromacs   | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 436.cactusADM | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 437.leslie3d  | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 444.namd      | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 447.dealII    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 450.soplex    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 453.povray    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 454.calculix  | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 459.GemsFDTD  | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 465.tonto     | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 470.lbm       | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 481.wrf       | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |
| 482.sphinx3   | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    | NC      | NC    |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

each process to unlimited using "ulimit -s unlimited"

## Platform Notes

```

BIOS configuration:
Set Power Efficiency Mode to Custom
Set Snoop Mode to ES mode
Set Patrol Scrub to Disable
Set Hyper-Threading to Disable
Sysinfo program /spec16/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 $$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Tue Feb 16 03:37:30 2016

```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 =

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 =

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Feb-2016  
Hardware Availability: Mar-2016  
Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
[http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2)**>SPEC CPU run**  
**up policy on** <https://www.spec.org/osg/policy.html#AppendixC>**>gener**

## Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen from some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sinfo>

```
From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E5-2630 v4 @ 2.20GHz
 2 "physical id"s (chips)
 20 "processors"
cores, siblings (Caution: containing these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores      : 10
  siblings       : 10
  physical 0:    : cores 0 1 2 3 4 8 9 10 11 12
  physical 1:    : cores 0 1 2 3 4 8 9 10 11 12
cache size      : 25600 KB
```

```
From /proc/meminfo
MemTotal:        26357072 kB
HugePages_Total: 0
Hugepagesize:    48 kB
```

```
From /etc/*release* /etc/*version*
os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.0 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.0"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server
```

```
uname -a:
Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT 2014 x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Feb 15 12:57
```

```
SPEC is set to: /spec16
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 =

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 =

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Feb-2016  
Hardware Availability: Mar-2016  
Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
[http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Platform Notes (Continued)

```
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda3       xfs   443G  12G  431G   3% /
Additional information from dmidecode:
```

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Insyde Corp. 7.11 02/14/2016

Memory:

```
8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz, configured at 2133 MHz
8x Samsung M393A2G40EB1-CRC 16 GB 2 rank 2400 MHz, configured at 2133 MHz
```

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,compact,1,0"
LD_LIBRARY_PATH = "/spec16/libs/32:/spec16/libs/64:/spec16/sh"
OMP_NUM_THREADS = "10"
```

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using Red Hat EL 7.1

Transparent Huge Pages enabled with:

```
echo always /sys/kernel/mm/transparent_hugepage/enabled
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

The Huawei XH622 V3 and Huawei XH628 V3 and Huawei XH620 V3

are functionally equivalent.

The results have been measured on a Huawei XH620 V3 model

## Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 =

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 =

CPU2006 license: 3175  
Test sponsor: Huawei  
Tested by: Huawei

Test date: Feb-2016  
Hardware Availability: Mar-2016  
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Base Compiler Invocation (Continued)

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.lelie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
483.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = **NC**

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = **NC**

CPU2006 license: 3175

Test date: Feb-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -fno-alias  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = **NC**

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = **NC**

CPU2006 license: 3175

Test date: Feb-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Peak Optimization Flags (Continued)

447.deallI: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tomcat: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

Continued on next page





# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = **NC**

Huawei XH622 V3(Intel Xeon E5-2630 v4)

SPECfp\_base2006 = **NC**

CPU2006 license: 3175

Test date: Feb-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
**up policy on** [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) **SPEC CPU run**  
**up policy on** <https://www.spec.org/osg/policy.html#AppendixC> **gener**

## Peak Optimization Flags (Continued)

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html>

You can also download the XML flags source by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Fri Oct 21 16:05:47 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 7 April 2016.