



# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp®\_rate2006 = NC

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = NC

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**

**up policy on [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run and reporting policy on <https://www.spec.org/osg/policy.html#AppendixC> general**

	Copies
410.bwaves	
416.gamess	
433.milc	
434.zeusmp	
435.gromacs	
436.cactusADM	
437.leslie3d	
444.namd	
447.dealII	
450.soplex	
453.povray	
454.calculix	
459.GemsFDTD	
465.tonto	
471.lbm	
481.wrf	
482.sphinx3	

**Non-Compliant**



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**

**compliant with the SPEC CPU run and reporting rules. See [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) for more information. See <https://www.spec.org/osg/policy.html#AppendixC> for the SPEC CPU run and reporting rules.**

Hardware		Software	
CPU Name:	Intel Xeon E5-2609 v4	Operating System:	Red Hat Enterprise Linux Server release 7.0 (Maipo)
CPU Characteristics:		Kernel:	3.10.0-123.el7.x86_64
CPU MHz:	1700	Compiler:	C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux; Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux
FPU:	Integrated	Architecture:	No
CPU(s) enabled:	16 cores, 2 chips, 8 cores/chip	File System:	ext4
CPU(s) orderable:	1,2 chip	System State:	Run level 3 (multi-user)
Primary Cache:	32 KB I + 32 KB D on chip per core	Base Pointers:	32/64-bit
Secondary Cache:	256 KB I+D on chip per core	Peak Pointers:	32/64-bit
L3 Cache:	20 MB I+D on chip per chip	Other Software:	None
Other Cache:	None		
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2400R, running at 1866 MHz)		
Disk Subsystem:	1 x 2 T SATA, 7200 RPM		
Other Hardware:	None		

**Non-Compliant**



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
416.gamess	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
433.milc	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
434.zeusmp	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
435.gromacs	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
436.cactusADM	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
437.leslie3d	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
444.namd	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
447.dealII	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
450.soplex	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
453.povray	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
454.calculix	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
459.GemsFDTD	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
465.tonto	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
470.lbm	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
481.wrf	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		
482.sphinx3	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = NC

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = NC

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Platform Notes

BIOS configuration:

Set Power Efficiency Mode to Performance

Set Snoop Mode to ES mode

Set Patrol Scrub to Disable

Sysinfo program /speccpu/spec16/config/sysinfo.rev.024

\$Rev: 6914 \$ \$Date:: 2014-06-25 # \$ e3fbb86675a285932ceab81e28219e1

running on localhost.localdomain Tue Mar 8 12:15:13 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2609 v4 @ 1.70GHz

2 "physical id"s (chips)

16 "processors"

cores, siblings (Caution: reporting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 8

siblings : 8

physical 0: cores 0 1 2 3 4 5 6 7

physical 1: cores 0 2 3 4 5 6 7

cache size : 2048 KB

From /proc/meminfo

MemTotal: 63571176 kB

HugePages\_Total: 0

HugePages\_Size: 2048 kB

From /etc/\*-release\* /etc/\*version\*

NAME="Red Hat Enterprise Linux Server"

VERSION="7.0 (Maipo)"

ID="rhel"

LIKE="fedora"

VERSION\_ID="7.0"

PRETTY\_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"

ANSI\_COLOR="0;31"

CPE\_NAME="cpe:/o:redhat:enterprise\_linux:7.0:GA:server"

redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)

system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)

system-release-cpe: cpe:/o:redhat:enterprise\_linux:7.0:ga:server

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org/>

Page 4



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Platform Notes (Continued)

```
uname -a:
Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
EDT 2014 x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Mar 7 05:24
```

```
SPEC is set to: /speccpu/spec16
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2        ext4  1.6T  39G  1.5T   2% /
Additional information from dmidecode:
```

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

```
BIOS Insyde Corp. 3.09 02/20/2014
Memory:
8x NO DIMM NO DIMM 3 rank
8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz, configured at 1867 MHz
8x Samsung M393A2G40EB1-CRC 16 GB 2 rank 2400 MHz, configured at 1867 MHz
```

(End of data from dmidecode program)

## General Notes

Environment variable set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/speccpu/spec16/libs/32:/speccpu/spec16/libs/64:/speccpu/spec16/sh"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB  
RedHat EL 7.1

Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/transparent\_hugepage/enabled

Filesystem page cache cleared with:  
echo 1 > /proc/sys/vm/drop\_caches  
runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
The Huawei CH121 V3 and Huawei CH222 V3
are electronically equivalent.
```

The results have been measured on a Huawei CH121 V3 model



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

## Base Compiler Invocation

C benchmarks:  
icc -m64

C++ benchmarks:  
icpc -m64

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tomcat: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wt: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

## Base Optimization Flags (Continued)

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not**  
a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run  
up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

## Peak Optimization Flags (Continued)

482.sphinx3: basepeak = yes

### C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafepass1  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafepass1  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafepass1  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.geusmp: basepeak = yes

437.leslie3d: basepeak = yes

439.gemsi BTD: basepeak = yes

465.tonto: -xCORE-AVX2(pass 2) -prof-gen:threadsafepass1  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4 -auto  
-inline-calloc -opt-malloc-options=3

### Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AVX2(pass 2) -prof-gen:threadsafepass1  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -opt-prefetch -auto-ilp32

Continued on next page





# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECfp\_rate2006 = **NC**

Huawei CH222 V3 (Intel Xeon E5-2609 v4)

SPECfp\_rate\_base2006 = **NC**

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not [http://spec.org/cpu2006/Docs/runrules.html#rule\\_1.3.2](http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2) SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

## Peak Optimization Flags (Continued)

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic70-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic70-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Fri Oct 21 20:22:24 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 April 2016.