



# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Gigabyte Technology Co., Ltd.

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

SPECfp®2006 = 115

SPECfp\_base2006 = 113

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: May-2016

Software Availability: Nov-2015



## Hardware

CPU Name: Intel Core i7-6950X  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 10 cores, 1 chip, 10 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

## Software

Operating System: Microsoft Windows 10 Pro  
 10.0.10586 N/A Build 10586  
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;  
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013  
 Auto Parallel: Yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Gigabyte Technology Co., Ltd.

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

SPECfp2006 = 115

SPECfp\_base2006 = 113

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: May-2016

Software Availability: Nov-2015

L3 Cache: 25 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (4 x 8 GB 2Rx4 PC4-2133R-U)  
Disk Subsystem: 1 TB Seagate SATA HDD, 7200 RPM  
Other Hardware: None

File System: NTFS  
System State: Default  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	50.8	267	<b>50.5</b>	<b>269</b>	50.5	269	50.8	267	<b>50.5</b>	<b>269</b>	50.5	269
416.gamess	408	47.9	410	47.7	<b>409</b>	<b>47.9</b>	388	50.4	<b>388</b>	<b>50.4</b>	388	50.5
433.milc	111	83.1	111	82.5	<b>111</b>	<b>82.6</b>	111	83.1	111	82.5	<b>111</b>	<b>82.6</b>
434.zeusmp	34.2	266	<b>34.2</b>	<b>266</b>	34.2	266	34.2	266	<b>34.2</b>	<b>266</b>	34.2	266
435.gromacs	102	70.2	99.3	71.9	<b>101</b>	<b>71.0</b>	102	70.2	99.3	71.9	<b>101</b>	<b>71.0</b>
436.cactusADM	<b>17.2</b>	<b>694</b>	17.3	693	17.2	696	<b>17.2</b>	<b>694</b>	17.3	693	17.2	696
437.leslie3d	<b>41.9</b>	<b>224</b>	41.7	225	42.1	223	<b>41.9</b>	<b>224</b>	41.7	225	42.1	223
444.namd	225	35.6	225	35.7	<b>225</b>	<b>35.7</b>	220	36.4	<b>220</b>	<b>36.4</b>	220	36.4
447.dealII	<b>169</b>	<b>67.7</b>	169	67.7	169	67.7	<b>169</b>	<b>67.7</b>	169	67.7	169	67.7
450.soplex	153	54.7	153	54.5	<b>153</b>	<b>54.5</b>	153	54.7	153	54.5	<b>153</b>	<b>54.5</b>
453.povray	79.0	67.3	78.5	67.8	<b>78.6</b>	<b>67.7</b>	66.3	80.3	<b>66.1</b>	<b>80.5</b>	65.9	80.7
454.calculix	122	67.8	<b>122</b>	<b>67.9</b>	121	67.9	122	67.8	<b>122</b>	<b>67.9</b>	121	67.9
459.GemsFDTD	68.5	155	68.3	155	<b>68.5</b>	<b>155</b>	68.5	155	68.3	155	<b>68.5</b>	<b>155</b>
465.tonto	184	53.5	<b>184</b>	<b>53.5</b>	184	53.4	176	56.0	177	55.5	<b>176</b>	<b>55.8</b>
470.lbm	38.2	360	<b>38.2</b>	<b>360</b>	38.3	359	38.2	360	<b>38.2</b>	<b>360</b>	38.3	359
481.wrf	<b>73.3</b>	<b>152</b>	72.8	154	73.7	152	<b>73.3</b>	<b>152</b>	72.8	154	73.7	152
482.sphinx3	<b>195</b>	<b>100</b>	195	99.8	194	100	<b>195</b>	<b>100</b>	195	99.8	194	100

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:  
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

## Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on Clt1C1B0D05C2E5 Sat Jun 18 11:59:34 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**Gigabyte Technology Co., Ltd.**

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

**SPECfp2006 = 115**

**SPECfp\_base2006 = 113**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Jun-2016

**Hardware Availability:** May-2016

**Software Availability:** Nov-2015

## Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 10 Pro
OS Version    : 10.0.10586 N/A Build 10586
System Manufacturer: Gigabyte Technology Co., Ltd.
System Model  : Default string
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 79 Stepping 1 GenuineIntel ~3001 Mhz
BIOS Version  : American Megatrends Inc. F2, 5/22/2016
Total Physical Memory: 32,606 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 2560
L3CacheSize   : 25600
MaxClockSpeed : 3001
Name          : Intel(R) Core(TM) i7-6950X CPU @ 3.00GHz
NumberOfCores : 10
NumberOfLogicalProcessors: 20
```

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

```
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit
```



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**Gigabyte Technology Co., Ltd.**

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

**SPECfp2006 = 115**

**SPECfp\_base2006 = 113**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Jun-2016

**Hardware Availability:** May-2016

**Software Availability:** Nov-2015

## Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 -names:lowercase /assume:underscore  
 437.leslie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 -DSPEC\_CPU\_BOOST\_CONFIG\_MSC\_VER -DSPEC\_NEED\_ALGORITHM  
 450.soplex: -DSPEC\_CPU\_P64 -DSPEC\_GETLINE\_TEST  
 453.povray: -DSPEC\_CPU\_P64  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER -names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch -Qcxx-features /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Gigabyte Technology Co., Ltd.

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

SPECfp2006 = 115

SPECfp\_base2006 = 113

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: May-2016

Software Availability: Nov-2015

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

## Peak Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: basepeak = yes

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 5



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**Gigabyte Technology Co., Ltd.**

(Test Sponsor: Intel Corporation)

GigaByte GA-X99-Designare EX motherboard (Intel Core i7-6950X)

**SPECfp2006 = 115**

**SPECfp\_base2006 = 113**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Jun-2016

**Hardware Availability:** May-2016

**Software Availability:** Nov-2015

## Peak Optimization Flags (Continued)

```
453.povray: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000
            shlW64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

410.bwaves: basepeak = yes

```
416.gamess: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
            -Qscalar-rep- /F1000000000
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-alloc
            /F1000000000
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Oct 4 14:49:39 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 4 October 2016.