



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Cisco Systems


SPEChpc 2021_sml_base = 1.32

Cisco UCS C245 M8 (AMD EPYC 9754)

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: May-2024
Hardware Availability: Jun-2024
Software Availability: Feb-2024



Results Table

Benchmark	Base										Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	
605.lbm_s	MPI	256	1	782	1.98	783	1.98	781	1.98										
613.soma_s	MPI	256	1	925	1.73	926	1.73	926	1.73										
618.tealeaf_s	MPI	256	1	3097	0.662	3096	0.662	3096	0.662										
619.clvleaf_s	MPI	256	1	2337	0.706	2338	0.706	2338	0.706										
621.miniswp_s	MPI	256	1	456	2.41	455	2.42	461	2.39										
628.pot3d_s	MPI	256	1	2537	0.660	2535	0.661	2537	0.660										
632.sph_exa_s	MPI	256	1	597	3.85	598	3.85	597	3.85										
634.hpgmgfv_s	MPI	256	1	1212	0.804	1212	0.805	1212	0.805										
635.weather_s	MPI	256	1	1675	1.55	1677	1.55	1677	1.55										

SPEChpc 2021_sml_base = 1.32

SPEChpc 2021_sml_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPEChpc 2021_sml_base = 1.32

Cisco UCS C245 M8 (AMD EPYC 9754)

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: May-2024
Hardware Availability: Jun-2024
Software Availability: Feb-2024

Hardware Summary

Type of System: Homogenous
Compute Node: Cisco UCS C245 M8
Compute Nodes Used: 1
Total Chips: 2
Total Cores: 256
Total Threads: 512
Total Memory: 1536 GB
Max. Peak Threads: --

Software Summary

Compiler: Intel oneAPI DPC++/C++ Compiler 2024.0.2
MPI Library: Intel MPI Library for Linux OS, Build 20231005
Other MPI Info: None
Other Software: None
Base Parallel Model: MPI
Base Ranks Run: 256
Base Threads Run: 1
Peak Parallel Models: Not Run
Minimum Peak Ranks: --
Maximum Peak Ranks: --
Max. Peak Threads: --
Min. Peak Threads: --

Node Description: Cisco UCS C245 M8

Hardware

Number of nodes: 1
Uses of the node: compute
Vendor: Cisco Systems
Model: Cisco UCS C245 M8
CPU Name: AMD EPYC 9754
CPU(s) orderable: 1,2 chips
Chips enabled: 2
Cores enabled: 256
Cores per chip: 128
Threads per core: 2
CPU Characteristics: Max. Boost Clock upto 3.1GHz
CPU MHz: 2250
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 256 MB I+D on chip per chip
16 MB shared / 8 cores
Other Cache: None
Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-5600B-R, running at 4800 MHz)
Disk Subsystem: 1 x 960 GB NVMe SSD
Other Hardware: None
Accel Count: 0
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: None
Number of Adapters: 0
Slot Type: None
Data Rate: None

Software

Accelerator Driver: --
Adapter: None
Adapter Driver: None
Adapter Firmware: None
Operating System: SUSE Linux Enterprise Server 15 SP5
Kernel 5.14.21-150500.53-default
Local File System: xfs
Shared File System: None
System State: Multi-user, run level 3
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPEChpc 2021_sml_base = 1.32

Cisco UCS C245 M8 (AMD EPYC 9754)

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: May-2024
Hardware Availability: Jun-2024
Software Availability: Feb-2024

Node Description: Cisco UCS C245 M8

Hardware (Continued)

Ports Used: 0
Interconnect Type: None

Submit Notes

The config file option 'submit' was used.
mpirun --bind-to core:overload-allowed --oversubscribe --mca topo basic -np \$ranks \$command

General Notes

MPI startup command:
mpirun command was used to start MPI jobs.

Compiler Version Notes

=====
CXXC 632.sph_exa_s(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler 2024.0.2 (2024.0.2.20231213)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /home/intel_tools/compiler/compiler/2024.0/bin/compiler
Configuration file:
/home/intel_tools/compiler/compiler/2024.0/bin/compiler/./icpx.cfg
=====

=====
CC 605.lbm_s(base) 613.soma_s(base) 618.tealeaf_s(base) 621.miniswp_s(base)
634.hpgmgfv_s(base)
=====

Intel(R) oneAPI DPC++/C++ Compiler 2024.0.2 (2024.0.2.20231213)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /home/intel_tools/compiler/compiler/2024.0/bin/compiler
Configuration file:
/home/intel_tools/compiler/compiler/2024.0/bin/compiler/./icx.cfg
=====

=====
FC 619.clvleaf_s(base) 635.weather_s(base)
=====

ifx (IFX) 2024.0.2 20231213
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPEChpc 2021_sml_base = 1.32

Cisco UCS C245 M8 (AMD EPYC 9754)

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: May-2024
Hardware Availability: Jun-2024
Software Availability: Feb-2024

Compiler Version Notes (Continued)

FC 628.pot3d_s(base)

ifx: command line warning #10157: ignoring option '-W'; argument is of wrong type

ifx (IFX) 2024.0.2 20231213

Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpiicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

Base Portability Flags

605.lbm_s: -lstdc++
613.soma_s: -lstdc++
618.tealeaf_s: -lstdc++
619.cvlleaf_s: -lstdc++
621.miniswp_s: -lstdc++
628.pot3d_s: -lstdc++
632.sph_exa_s: -lstdc++
634.hpgmgfv_s: -lstdc++
635.weather_s: -lstdc++

Base Optimization Flags

C benchmarks:

-Ofast -ipo -mprefer-vector-width=512 -march=common-avx512
-ansi-alias

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2024 Standard Performance Evaluation Corporation

Cisco Systems

SPEChpc 2021_sml_base = 1.32

Cisco UCS C245 M8 (AMD EPYC 9754)

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 9019
Test Sponsor: Cisco Systems
Tested by: Cisco Systems

Test Date: May-2024
Hardware Availability: Jun-2024
Software Availability: Feb-2024

Base Optimization Flags (Continued)

C++ benchmarks:

-Ofast -ipo -mprefer-vector-width=512 -march=common-avx512
-ansi-alias

Fortran benchmarks:

-Ofast -ipo -mprefer-vector-width=512 -march=common-avx512
-nostandard-realloc-lhs -align array64byte

Base Other Flags

Fortran benchmarks:

628.pot3d_s: -Wno-incompatible-function-pointer-types

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags_hpc.2024.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags_hpc.2024.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.8 on 2024-04-17 09:31:01-0400.
Report generated on 2024-05-29 12:43:02 by hpc2021 PDF formatter v1.0.3.
Originally published on 2024-05-29.