



# OMPL2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

NEC  
NEC TX7 i9510 (1500MHz, Itanium 2)

SPECompLpeak2001 = --  
SPECompLbase2001 = 183248

SPEC license #PG0057A | Tested by: HLRS | Test site: HLRS | Test date: Jan-2005 | Hardware Avail: Jan-2004 | Software Avail: Dec-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
311.wupwise_1	9200	767	191950			
313.swim_1	12500	1573	127116			
315.mgrid_1	13500	1317	163968			
317.applu_1	13500	1094	197431			
321.quake_1	13000	1559	133439			
325.apsi_1	10500	817	205720			
327.gafort_1	11000	1068	164746			
329.fma3d_1	23500	2057	182772			
331.art_1	25000	1121	356858			

### Hardware

CPU: Intel Itanium 2  
 CPU MHz: 1500  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 32 chips, 1 core/chip  
 CPU(s) orderable: 8-32  
 Primary Cache: 16KBI + 16KBD (on chip) per CPU  
 Secondary Cache: 256KB (on chip) per CPU  
 L3 Cache: 6.0MB (on chip) per CPU  
 Other Cache: N/A  
 Memory: 512 GB  
 Disk Subsystem: Seagate ST373307LC  
 Other Hardware: None

### Software

OpenMP Threads: 32  
 Parallel: OpenMP  
 Operating System: NEC Linux 3.4  
 Compiler: Intel(R) Fortran Compiler for Linux 8.1 Build 20041123  
 Intel(R) C++ Compiler for Linux 8.1 Build 20041123  
 File System: ext2 filesystem  
 System State: Multi-user

## Notes/Tuning Information

Tested by HLRS

Portability Flags:  
 318.galgel\_m: -FI -132

Extra Flags:  
 330.art\_m: -DINTS\_PER\_CACHELINE=32 -DDBLS\_PER\_CACHELINE=16

Baseline user environment:  
 OMP\_NUM\_THREADS 32  
 limit stacksize 64000  
 KMP\_STACKSIZE 31M  
 KMP\_LIBRARY TURNAROUND  
 OMP\_DYNAMIC FALSE  
 KMP\_SCHEDULE static,balanced

For all benchmarks threads were bound to cores using the following submit command:  
 fplace -r -o 1,2 \$command,  
 This instructs fplace to skip placement of the lightweight  
 OpenMP monitor thread, which is created prior to the

For a description of HLRS's compiler flags, portability flags, and  
 system parameters used to generate this result, please refer to the  
 HLRS-20050119-Linux-Intel8.1-IPF.txt file in the flags directory.