



# OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 520 (1900 MHz, 2 CPU)

SPECompMpeak2001 = 8174

SPECompMbase2001 = 8141

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Sep-2005 | Hardware Avail: Oct-2005 | Software Avail: Oct-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	665	9022	665	9022
312.swim_m	6000	779	7705	774	7752
314.mgrid_m	7300	1784	4091	1784	4091
316.applu_m	4000	467	8563	416	9604
318.galgel_m	5100	321	15869	326	15658
320.earthquake_m	2600	225	11559	244	10634
324.apsi_m	3400	480	7081	480	7081
326.gafort_m	8700	1065	8167	1065	8167
328.fma3d_m	4600	1118	4113	1118	4113
330.art_m	6400	324	19758	324	19758
332.ammp_m	7000	1411	4960	1384	5059

Hardware	Software
CPU: POWER5+	OpenMP Threads: 4
CPU MHz: 1900	Parallel: OpenMP
FPU: Integrated	Operating System: AIX 5L V5.3
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (SMT on)	Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX XL Fortran Enterprise Edition Version 10.1 for AIX Other Software: ESSL 4.2.0.2
CPU(s) orderable: 2	File System: AIX/JFS2
Primary Cache: 64KBI+32KBD (on chip)	System State: Multi-user
Secondary Cache: 1920KB unified (on chip)	
L3 Cache: 36MB unified (off-chip)/DCM, 1 DCM/SUT	
Other Cache: None	
Memory: 8x2GB	
Disk Subsystem: 1x73GB SCSI, 15K RPM	
Other Hardware: None	

## Notes/Tuning Information

Tested by IBM

### Portability Flags & Environment Variables

-qfixed used in: 310.wupwise\_m, 312.swim\_m, 314.mgrid\_m, 316.applu\_m, 324.apsi\_m  
 -qfixed=80 used in: 318.galgel\_m  
 -qsuffix=f=f90 used in: 318.galgel\_m, 326.gafort\_m, 328.fma3d\_m

### Base Flags

C: -qpdf1/pdf2  
 -q64 -O5 -blpdata -qalign=natural -qhot=arraypad -Q -qsmp=omp  
 EXTRA\_LDFLAGS=-q64  
 FORTRAN: -O5 -qipa=noobject -qmaxmem=-1 -qsmp=omp  
 EXTRA\_LDFLAGS=-bmaxdata:0x80000000

### Base & Peak User Environment:

OMP\_NUM\_THREADS=4  
 OMP\_DYNAMIC=FALSE  
 XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=1  
 MALLOCMULTIHEAP=1

### Peak Flags:

-qsmp=omp used in all cases  
 310.wupwise\_m: basepeak=1



# OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 520 (1900 MHz, 2 CPU)

SPECompMpeak2001 = 8174

SPECompMbase2001 = 8141

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Sep-2005 | Hardware Avail: Oct-2005 | Software Avail: Oct-2005

## Notes/Tuning Information (Continued)

```

312.swim_m:      -O5 -blpdata -lmass
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
314.mgrid_m:    basepeak=1
316.applu_m:    -O5 -blpdata -lmass
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
318.galgel_m:   -O3 -qhot -qarch=pwr4 -qtune=pwr4 -blpdata
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
320.earthquake_m: -O5 -lesslsm
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
325.apsi_m:     basepeak=1
326.gafort_m:   basepeak=1
328.fma3d_m:    basepeak=1
330.art_m:      basepeak=1
332.ammp_m:     -qpdf1/pdf2
                  -O5 -blpdata -qfdpr -qalign=natural
                  fdpr -q -O3

```

### Alternate sources:

Add critical region around update of linked list in parallel loop.  
 Approved src.alt available as ompm-purdue1-20040324.tar.gz  
 Used for 330.art\_m, base and peak.

### Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used  
 with 312.swim\_m, 316.applu\_m, 320.earthquake\_m.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

ESSL: Engineering and Scientific Subroutine Library

SUT: Acronym for "System Under Test"

C: IBM XL C for AIX invoked as xlc\_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf90\_r

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=400 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```

The default number of executing threads is set as follows:

```
export OMP_NUM_THREADS=4
```

Use flags-description file IBM-20051013-AIX.txt.