



OMPL2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

SGI

SGI Altix 4700 Density System (1600MHz 24M L3, DC Itanium2 9050)

SPECompLpeak2001 = 1005076

SPECompLbase2001 = 987139

SPEC license #HPG0014 | Tested by: SGI | Test site: SGI | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jul-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
311.wupwise_1	9200	85.7	1717280	85.7	1717280
313.swim_1	12500	124	1606568	124	1606568
315.mgrid_1	13500	283	764544	258	837444
317.applu_1	13500	297	727215	297	727215
321.quake_1	13000	472	440372	472	440372
325.apsi_1	10500	187	900515	174	966762
327.gafort_1	11000	300	587544	300	587544
329.fma3d_1	23500	496	758395	496	758395
331.art_1	25000	122	3283637	122	3283637

Hardware

CPU: Intel DC Itanium2 Processor 9050
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 256 cores, 128 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 2-1024 cores
Primary Cache: 16KBI + 16KBD (on chip) per core
Secondary Cache: 1MBI + 256KBD (on chip) per core
L3 Cache: 12.0MB (on chip) per core
Other Cache: N/A
Memory: 512 GB (8*1G PC3200 DIMMS per 4 core module)
Disk Subsystem: 1 x 147 GB SCSI (Seagate Cheetah 10k rpm)
Other Hardware: None

Software

OpenMP Threads: 256
Parallel: OpenMP
Operating System: SUSE Linux Enterprise Server 10 + SGI ProPack(TM) 5
Compiler: Intel(R) Fortran Compiler for Linux 9.1 (Build 20060707)
Intel(R) C++ Compiler for Linux 9.1 (Build 20060707)
File System: xfs
System State: Multi-user

Notes/Tuning Information

Baseline optimization flags:

C programs: -openmp -O3 -IPF_fp_relaxed -ipo -ansi_alias (ONESTEP)
Fortran programs: -openmp -O3 -IPF_fp_relaxed -ipo (ONESTEP)
OpenMP runtime library libguide.a statically linked

Extra Flags:

331.art_1: -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16

User environment:

OMP_NUM_THREADS 256
limit stacksize 128000
KMP_STACKSIZE 124M
KMP_LIBRARY TURNAROUND
OMP_DYNAMIC FALSE
KMP_SCHEDULE static,balanced

Peak optimization flags

311.wupwise_1: basepeak=true
313.swim_1: basepeak=true
315.mgrid_1: -openmp -O3 -IPF_fp_relaxed -ipo
OpenMP runtime library libguide.a statically linked
OMP_NUM_THREADS = 128
submit = dplace -x2 -e -c255-0:2 \$command
317.applu_1: basepeak=true
321.quake_1: basepeak=true
325.apsi_1: -openmp -O3 -IPF_fp_relaxed -ipo



OMPL2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

SGI

SGI Altix 4700 Density System (1600MHz 24M L3, DC Itanium2 9050)

SPECompLpeak2001 = 1005076

SPECompLbase2001 = 987139

SPEC license #HPG0014 | Tested by: | SGI | Test site: | SGI | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jul-2006

Notes/Tuning Information (Continued)

OpenMP runtime library libguide.a statically linked

OMP_NUM_THREADS = 128

submit = dplace -x2 -e -c255-0:2 \$command

327.gafort_1: basepeak=true

329.fma3d_1: basepeak=true

331.art_1: basepeak=true

Required alternate sources:

Add critical region around update of linked list in parallel loop.

Approved src.alt available as omp1-purduel-20040324.tar.gz

Used for 331.art_1, base and peak.

For all benchmarks threads were bound to cores using the following submit command:

```
dplace -x2 -e -cNTM1,0 $command,
```

where NTM1 is the number of threads minus 1.

This binds threads in order of creation, beginning with the master thread on core NTM1, the first slave thread on core NTM1-1, and so on.

The -x2 flag instructs dplace to skip placement of the lightweight OpenMP monitor thread, which is created prior to the slave threads.

For a description of SGI's compiler flags, portability flags, and system parameters used to generate this result, please refer to the SGI-20060801-Linux-Intel9.1-IPF.txt file in the flags directory.