



OMPM2001 Result

Copyright ©1999-2001, Standard Performance Evaluation Corporation

SGI
SGI Origin 3800 64X 500MHz R14k

SPECompMpeak2001 = 17826

SPECompMbase2001 = 15758

SPEC license #HPG0014 | Tested by: SGI | Test site: | Test date: Jun-2001 | Hardware Avail: Jun-2001 | Software Avail: Mar-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	218	27572	211	28475	
312.swim_m	6000	258	23268	252	23843	
314.mgrid_m	7300	281	25964	280	26046	
316.applu_m	4000	184	21730	131	30440	
318.galgel_m	5100	661	7712	553	9222	
320.quake_m	2600	275	9461	179	14512	
324.apsi_m	3400	216	15720	156	21821	
326.gafort_m	8700	601	14465	590	14750	
328.fma3d_m	4600	339	13560	343	13425	
330.art_m	6400	343	18667	346	18471	
332.ammp_m	7000	715	9789	697	10045	

Hardware

CPU: R14000
CPU MHz: 500
FPU: Integrated
CPU(s) enabled: 64
CPU(s) orderable: 2-512
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 64 GB
Disk Subsystem: 1 x 18 GB FC, 4x 36 GB (striped) FC
Other Hardware: None

Software

OpenMP Threads: 64
Parallel: --
Operating System: IRIX 6.5.12m
Compiler: MIPSpro 7.3.1.2m C, Fortran90
File System: xfs
System State: Multi-user

Notes/Tuning Information

Baseline flags: -64 -mp -Ofast=ip35 -LNO:fusion=2

Portability Flags:

318.galgel_m: -fixedform -extend_source

Peak flags:

310.wupwise_m: -64 -mp -Ofast=ip27 -LNO:fusion=2:prefetch Ahead=5 -INLINE:aggressive=on

. -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000 -OPT:Olimit=0

312.swim_m: -64 -mp -Ofast=ip35 -LNO:fusion=2

314.mgrid_m: -64 -mp -Ofast=ip35 -LNO:fusion=2

316.applu_m: -64 -mp -Ofast=ip35 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2

. -CG:ld_latency=3

318.galgel_m: -64 -mp -Ofast=ip35 -LNO:fusion=2

320.quake_m: -64 -mp -Ofast=ip35 -OPT:goto=off:unroll_size=160:unroll_times_max=4

. -CG:ld_latency=3

324.apsi_m: -64 -mp -Ofast=ip35 -LNO:fusion=2 -TENV:X=4 -LNO:prefetch=0:blocking=off

326.gafort_m: -64 -mp -Ofast=ip35

328.fma3d_m: -64 -mp -Ofast=ip35 -LNO:fusion=2 -CG:ld_latency=3

. -IPA:linear=on:use_intrinsic

330.art_m: -64 -mp -Ofast=ip35 -LNO:fusion=2

332.ammp_m: -64 -mp -Ofast=ip35 -LNO:fusion=2:prefetch=0

Baseline user environment:

limit stacksize 512m

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



OMPM2001 Result

Copyright ©1999-2001, Standard Performance Evaluation Corporation

SGI

SGI Origin 3800 64X 500MHz R14k

SPECompMpeak2001 = 17826

SPECompMbase2001 = 15758

SPEC license #HPG0014 Tested by: SGI Test site: Test date: Jun-2001 Hardware AvailJun-2001 Software AvailMar-2001

Notes/Tuning Information (Continued)

```
OMP_NUM_THREADS=64
OMP_DYNAMIC=FALSE
MPC_GANG=OFF
_DSM_MUSTRUN=
_DSM_WAIT=SPIN
```

Peak user environment:

```
316.applu_m: PAGESIZE_DATA=4096, PAGESIZE_STACK=4096, _DSM_PLACEMENT=ROUND_ROBIN
318.galgel_m: _DSM_PLACEMENT=ROUND_ROBIN, OMP_NUM_THREADS=40
320.equake_m: OMP_NUM_THREADS=48
324.apsi_m: PAGESIZE_DATA=4096, PAGESIZE_STACK=4096
332.ammp_m: PAGESIZE_DATA=1024, PAGESIZE_STACK=1024, _DSM_PLACEMENT=ROUND_ROBIN
```

The following O/S parameters were set via systune:

```
percent_totalmem_4m_pages = 25 ; percent_totalmem_1m_pages = 25
percent_totalmem_256k_pages = 10 ; percent_totalmem_64k_pages = 10
```