



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1500MHz, Itanium 2)

SPECompMpeak2001 = 35042

SPECompMbase2001 = 31276

SPEC license #HPG0014 | Tested by: SGI | Test site: SGI | Test date: Aug-2003 | Hardware Avail: Jun-2003 | Software Avail: Jul-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	72.6	82666	72.6	82666	
312.swim_m	6000	53.5	112087	53.5	112087	
314.mgrid_m	7300	218	33462	218	33462	
316.applu_m	4000	420	9535	342	11701	
318.galgel_m	5100	604	8440	462	11035	
320.earthquake_m	2600	112	23270	79.9	32552	
324.apsi_m	3400	86.5	39284	77.7	43782	
326.gafort_m	8700	313	27831	265	32834	
328.fma3d_m	4600	184	25039	155	29631	
330.art_m	6400	51.9	123248	51.9	123248	
332.ammp_m	7000	490	14299	490	14299	

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 64
 CPU(s) orderable: 4-64
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 6.0MB (on chip) per CPU
 Other Cache: N/A
 Memory: 128 GB (16*512MB DIMMS per 4cpu module)
 Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
 Other Hardware: None

Software

OpenMP Threads: 64
 Parallel: OpenMP
 Operating System: SGI ProPack(TM) v2.2
 Compiler: Intel(R) Fortran Compiler for Linux 7.1 (Build 20030701)
 Intel(R) C++ Compiler for Linux 7.1 (Build 20030701)
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags:

C programs: -openmp -O3 -ipo -ansi -ansi_alias (ONESTEP)
 Fortran programs: -openmp -O3 -ipo -stack_temps (ONESTEP)

Portability Flags:

318.galgel_m: -FI -132

Extra Flags:

330.art_m: -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16

Baseline user environment:

OMP_NUM_THREADS=64
 limit stacksize 64000
 KMP_STACKSIZE 31M
 KMP_LIBRARY TURNAROUND

Peak optimization flags:

310.wupwise_m: basepeak=true
 312.swim_m: basepeak=true
 314.mgrid_m: basepeak=true
 316.applu_m: -openmp -O3 -ipo -stack_temps (ONESTEP)
 OMP_NUM_THREADS=32
 318.galgel_m: -openmp -O3 -ipo -stack_temps (ONESTEP)



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

SGI

SGI Altix 3000 (1500MHz, Itanium 2)

SPECompMpeak2001 = 35042

SPECompMbase2001 = 31276

SPEC license #HPG0014 Tested by: SGI Test site: SGI Test date: Aug-2003 Hardware Avail: Jun-2003 Software Avail: Jul-2003

Notes/Tuning Information (Continued)

OMP_NUM_THREADS=32

```
320.equake_m: -openmp -O3 -ipo -ansi -ansi_alias (ONESTEP)
324.apsi_m: -openmp -O3 -ipo -stack_temps (ONESTEP)
326.gafort_m: -openmp -O3 -ipo -stack_temps (ONESTEP)
328.fma3d_m: -openmp -O3 -ipo -stack_temps (ONESTEP)
330.art_m: basepeak=true
332.amp_m: basepeak=true
```

Alternate sources:

ISO C and C++ compatible sources

Available as SPEC OMPM2001 source: ompm2001-isoc-20020619.tar.gz

Used for base: 320.equake_m, 330.art_m, 332.amp_m

and peak: 330.art_m, 332.amp_m

Peak sources:

SPEC OMPL2001 source for 64bit systems modified for SPEC OMPM2001.

Available as SPEC OMPM2001 Source: ompm2001-srcl64bit-20020807.tar.gz.

Used for 320.equake_m, 324.apsi_m, 326.gafort_m, and 328.fma3d_m.

For all benchmarks threads were bound to CPUs using the following submit command:

```
dplace -e -c0,x,x,1-NTM1 $command,
where NTM1 is the number of threads minus 1.
```