



OMPM2001 Result

Copyright ©1999-2008, Standard Performance Evaluation Corporation

ASUS Computer International
ASUS KFSN4-DRE

SPECompMpeak2001 = 18029
SPECompMbase2001 = 17598

SPEC license #HPG0017 | Tested by: Advanced Micro Devices | Test site: Austin TX | Test date: Mar-2008 | Hardware Avail: Apr-2008 | Software Avail: Nov-2007

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	251	23937	224	26825
312.swim_m	6000	432	13897	376	15971
314.mgrid_m	7300	435	16779	435	16779
316.applu_m	4000	320	12505	320	12505
318.galgel_m	5100	282	18073	282	18073
320.quake_m	2600	138	18895	138	18814
324.apsi_m	3400	156	21750	155	21971
326.gafort_m	8700	474	18363	474	18363
328.fma3d_m	4600	404	11395	404	11395
330.art_m	6400	126	50736	126	50736
332.ammp_m	7000	768	9109	763	9173

Software

OpenMP Threads: 8
Parallel: OpenMP
Operating System: SLES10 SP1 64bit
Compiler: PathScale Compiler Suite ver. 3.1
File System: Linux/Ext3
System State: Multi-User

Hardware

CPU: AMD Opteron Processor 2356
CPU MHz: 2300
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 512 KB I+D on chip per core
L3 Cache: 2 MB I+D on chip per chip
Other Cache: None
Memory: 16GB (8x2GB, PC2-5300 CL5 dual-rank)
Disk Subsystem: 160GB 7200 RPM SATA
Other Hardware: None

Notes/Tuning Information

Extra art Base Flags

330.art_m (extra): -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

Base tuning:

C : pathcc -mp -Ofast -mcmmodel=medium
Fortran : pathf90 -mp -Ofast -OPT:early_mp=on -mcmmodel=medium
ONESTEP=yes

Peak tuning:

310.wupwise_m: -mp -Ofast -msse3 -LNO:prefetch Ahead=5:prefetch=3
-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3
-IPA:linear=on:plimit=50000:callee_limit=5000
312.swim_m: -mp -O3 -OPT:Ofast -m3dnow -mcmmodel=medium -LNO:simd=0
314.mgrid_m: basepeak=yes
316.applu_m: basepeak=yes
318.galgel_m: basepeak=yes
320.quake_m: -Ofast -mp -OPT:alias=disjoint
324.apsi_m: -mp -O3 -OPT:Ofast -TENV:x=4 -LNO:fusion=2:prefetch=0
326.gafort_m: basepeak=yes
328.fma3d_m: basepeak=yes
330.art_m: basepeak=yes
332.ammp_m: -mp -Ofast -mcpu=opteron -mcmmodel=medium



OMPM2001 Result

Copyright ©1999-2008, Standard Performance Evaluation Corporation

ASUS Computer International
ASUS KFSN4-DRE

SPECompMpeak2001 = 18029

SPECompMbase2001 = 17598

SPEC license #HPG0017 | Tested by: Advanced Micro Devices | Test site: Austin TX | Test date: Mar-2008 | Hardware Avail: Apr-2008 | Software Avail: Nov-2007

Notes/Tuning Information (Continued)

Portability flags:

```
318.galgel_m : -fixedform -col80
```

Base and Peak User Environment (bash):

```
export OMP_NUM_THREADS=8
export OMP_DYNAMIC=FALSE
export PSC_OMP_AFFINITY=TRUE
export PSC_OMP_STATIC_FAIR=TRUE
export PSC_OMP_THREAD_SPIN=1000000000
ulimit -s unlimited
```

For flag descriptions, see file AMD-Apr2008-psc31_flags.txt
Phoenix BIOS version 2.02. Default BIOS settings used.