



OMPL2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4440 (AMD Opteron 8384 2.7GHz)

SPECompLpeak2001 = 175648
SPECompLbase2001 = 166853

SPEC license #HPG0010 | Tested by: Sun Microsystems | Test site: Menlo Park | Test date: Nov-2008 | Hardware Avail: Jan-2009 | Software Avail: Dec-2008

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
311.wupwise_l	9200	633	232634	582	252732
313.swim_l	12500	1858	107638	1852	108008
315.mgrid_l	13500	1185	182247	1179	183248
317.applu_l	13500	3393	63655	3362	64257
321.quake_l	13000	2207	94259	1684	123550
325.apsi_l	10500	866	194099	794	211629
327.gafort_l	11000	1161	151545	1160	151674
329.fma3d_l	23500	2042	184100	2021	186088
331.art_l	25000	592	675978	596	670932

Hardware		Software	
CPU:	AMD Opteron Processor 8384	OpenMP Threads:	16
CPU MHz:	2700	Parallel:	OpenMP and Automatic parallel
FPU:	Integrated	Operating System:	OpenSolaris 2008.11
CPU(s) enabled:	16 cores, 4 chips, 4 cores/chip	Compiler:	Sun Studio Express 11/08
CPU(s) orderable:	2,4 chips	File System:	OS on zfs, Benchmark on ufs
Primary Cache:	64 KB I + 64 KB D on chip per core	System State:	Multi-User
Secondary Cache:	512 KB I+D on chip per core		
L3 Cache:	6 MB I+D on chip per chip		
Other Cache:	None		
Memory:	64 GB (16x4GB, DDR2-667 CL5 ECC Registered)		
Disk Subsystem:	2 x SAS, 72 GB, 10 K RPM		
Other Hardware:	None		

Notes/Tuning Information

Compiler Invocation:

C : cc
F90 : f90
F77 : f90

Base tuning:

Fortran : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch -xprefetch_level=3 -m64 -lmtmalloc
C : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch -xprefetch_level=3 -m64 -lmtmalloc
ONESTEP=yes

Peak tuning:

ONESTEP=yes for all peak tests.

311.wupwise_l : -fast -xpagesize=2m -xmodel=medium -Qoption ube -sched_first_pass=1 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xvector=simd -xopenmp -lmvec

313.swim_l : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch -xprefetch_level=3 -m64 -lmtmalloc

315.mgrid_l : -fast -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch -xprefetch_level=3 -m64 -lmtmalloc

317.applu_l : -fast -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -Qoption f90comp -hoist_expensive,-hoist_trivial -qoption ube -memcpy_threshold2=64 -xprefetch -xprefetch_level=3 -m64 -lmtmalloc

321.quake_l : -fast -xmodel=medium -fns=no -xalias_level=layout -xdepend=no -xarch=amd64 -xopenmp -lmvec

325.apsi_l : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch -xprefetch_level=3 -m64 -lmtmalloc

327.gafort_l : -fast -xmodel=medium -fstore -aligncommon=8 -Qoption ube -sched_first_pass=1 -xpagesize=2m



OMPL2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4440 (AMD Opteron 8384 2.7GHz)

SPECompLpeak2001 = 175648
SPECompLbase2001 = 166853

SPEC license #HPG0010 | Tested by: Sun Microsystems | Test site: Menlo Park | Test date: Nov-2008 | Hardware Avail: Jan-2009 | Software Avail: Dec-2008

Notes/Tuning Information (Continued)

```
-xipo=2 -m64 -xvector=simd -xopenmp -lmvec
329.fma3d_1 : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch
             -xprefetch_level=3 -m64 -lmtmalloc
331.art_1   : -fast -xpagesize=2m -xmodel=medium -xopenmp -xautopar -xipo=2 -xvector=lib -xprefetch
             -xprefetch_level=3 -m64 -lmtmalloc
Extra art allowed flags:
331.art_1   : -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8
```

Base and Peak User Environment:

```
export OMP_NUM_THREADS=16
export SUNW_MP_PROCBIND=TRUE
export SUNW_MP_THR_IDLE=SPIN
export OMP_NESTED=FALSE
export STACKSIZE=16384
export OMP_DYNAMIC=TRUE
ulimit -s unlimited
```

For a description of Sun Studio 10 Compiler flags, portability flags and system parameters used to generate this result, please refer to SUN-20080827-Studio-Solaris-X86_64.txt file in the flags directory.

Default BIOS settings used.