



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

IBM Corporation
IBM Flex System p260 (4.1 GHz, 16 core, SLES)

SPECompMpeak2001 = 107007
SPECompMbase2001 = 92441

SPEC license #HPG0005 | Tested by: IBM Corporation | Test site: Austin, TX | Test date: Oct-2012 | Hardware Avail: Dec-2012 | Software Avail: Dec-2012

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	53.0	113125	53.0	113125
312.swim_m	6000	82.0	73189	76.4	78495
314.mgrid_m	7300	79.4	91991	73.2	99685
316.applu_m	4000	23.5	169966	21.2	188326
318.galgel_m	5100	78.4	65036	39.7	128463
320.quake_m	2600	34.9	74403	25.6	101702
324.apsi_m	3400	34.2	99317	34.2	99317
326.gafort_m	8700	135	64365	101	86422
328.fma3d_m	4600	86.5	53187	86.5	53187
330.art_m	6400	19.4	329558	19.4	329558
332.ampm_m	7000	117	60015	109	64284

Hardware	Software
CPU: POWER7+	OpenMP Threads: 64
CPU MHz: 4116	Parallel: OpenMP
FPU: Integrated	Operating System: SUSE Linux Enterprise Server 11 SP2 (3.0.13-0.27-ppc64)
CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 4 threads/core	Compiler: IBM XL C/C++ for Linux, V12.1 Version: 12.01.0000.0002
CPU(s) orderable: 16 cores	IBM XL Fortran for Linux, V14.1 Version: 14.01.0000.0002
Primary Cache: 32 KB I + 32 KB D on chip per core	Other Software: IBM Engineering and Scientific Subroutine Library for Linux on POWER, Version 5.1.0-2
Secondary Cache: 256 KB I+D on chip per core	File System: ext3
L3 Cache: 10 MB I+D on chip per core	System State: Run level 3 (multi-user)
Other Cache: None	
Memory: 128 GB (16 x 8 GB) DDR3 1066 MHz	
Disk Subsystem: 1 x 600 GB SAS SFF 10K RPM	
Other Hardware: None	

Notes/Tuning Information

Portability Flags Variables

-qfixed used in: 310.wupwise_m, 312.swim_m, 314.mgrid_m, 316.applu_m, 324.apsi_m
 -qfixed=80 used in: 318.galgel_m
 -qsuffix=f=f90 used in: 318.galgel_m 326.gafort_m, 328.fma3d_m

Base Flags

C: -O5 -q64 -qhot=arraypad -Q -qsmp=omp
 FORTRAN: -O5 -q64 -qhot=arraypad -Q -qsmp=omp

Base & Peak Environment Flags:

OMP_NUM_THREADS = 32
 OMP_DYNAMIC=FALSE
 XL SMP OPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:PROCS=0,1,4,5,8,9,12,13,16,17,20,21,24,25,28,29,32,33,36,37,40,41,44,45,48,49,52,53,56,57,60,61
 XLFRTEOPTS=intrinthds=1

Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used with 312.swim_m, 316.applu_m, 320.quake_m, 326.gafort_m

Peak Flags



OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

IBM Corporation
IBM Flex System p260 (4.1 GHz, 16 core, SLES)

SPECompMpeak2001 = 107007
SPECompMbase2001 = 92441

SPEC license #HPG0005 | Tested by: IBM Corporation | Test site: Austin, TX | Test date: Oct-2012 | Hardware Avail: Dec-2012 | Software Avail: Dec-2012

Notes/Tuning Information (Continued)

-qsmp=omp used in all cases

```

310.wupwise_m      basepeak = 1
312.swim_m:        -O3 -q32 -qpdf1/pdf2
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=4
                   OMP_NUM_THREADS = 16
314.mgrid_m:      -O5 -q64 -qhot=arraypad
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=4
                   OMP_NUM_THREADS = 16
316.applu_m:      -O3 -q64 -qpdf1/pdf2
                   -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=1
                   OMP_NUM_THREADS = 64
318.galgel_m:     -O5 -q64 -qessl
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:PROCS=0,4,8,12,16,20,24,28
                   OMP_NUM_THREADS = 8
                   EXTRA_LIBS=-lesslsm
320.equake_m:     -O5 -q64 -qpdf1/pdf
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=4
                   OMP_NUM_THREADS = 16
324.aspi_m:       basepeak = 1
326.gafort_m:     -O5 -q32 -qhot=arraypad
                   XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:STARTPROC=0:STRIDE=1
                   OMP_NUM_THREADS = 64
328.fma3d_m:      basepeak = 1
330.art_m:        basepeak = 1
332.ammp_m:       -O5 -q32 -qhot=arraypad -Q

```

kernel release 3.0.13-0.27-ppc64

Use flags-description file IBM-20121004-Linux.txt
ulimit -s (stack) set to 1048576.

Large pages reserved as follows by root user:
echo 480 > /proc/sys/vm/nr_hugepages
System configured with libhugetlbfs library for application access to large pages

Intelligent Energy Optimization enabled, up to 4.340 GHz
This Compute Node is housed in an "IBM Flex System Enterprise Chassis"

The following environment variables were set before the runspec command:
export HUGETLB_MORECORE=yes
export HUGETLB_VERBOSE=0
export HUGETLB_ELFMAP=RW
export HUGETLB_SHM=yes