



TAKING YOU FORWARD

Standard Interior



WWW. GOLDENDRAGONBUS.COM

XIAMEN GOLDEN DRAGON BUS CO.,LTD Add: No.69 Huli St.Huli Ind.Zone,Xiamen,Fujian,P.R.China Post code:361006
Tel:86-400-8867-866 86-592-5608977 Fax:86-592-5608979 Email: ied@goldendragonbus.com



XML6125 J12

Version 1,June,2017



Multi-Functional Dashboard



XML6120J12 Single Diff (front-mounted engine)

General Data			
Overall Length/Width/Height(mm)	12000X2550X3840mm		
Wheelbase(mm)	6200		
Overhang Front/Rear(mm)	2336/3459		
Angle of Approach/Departure	14°/10°		
Kerb/Gross Vehicle Weight	13,000Kg / 17,500Kg		
Turning Circle(m)	≤22m		
Drive Line			
Emission Control	EURO II		
Engine	Cummins L360 20 (diesel)		
Transmission	S6-160, 6 gear manual	6DS150T, 6 gear manual	ZF6S1610, 6 gear manual
Fuel Tank	400L	530L(option)	530L(option)
Chassis			
Front Axle	7T, disc type		
Rear Axle	13T, ratio 4.10, drum type		
Steering System	Hydraulic power steering		
Brake System	Double-circuit air brake, parking brake		
Auxiliary Brake	2400N/m eddy-current retarder		
Suspension	Multi-spring leaf		
Bodywork			
Bodywork Frame	Integral structure made of rectangular cross section steel tubes		
Front/Rear Panels	Square steel frame + fiber glass skin panel		
Side Panels	High density steel and aluminum sheets,E-coating for whole body		
Door Arrangement	Front	Middle (Option)	
Height of First Step(mm)	390	390	
Seating Capacity	66+1+1 (3+2)	53+1+1 (2+2)	
Roof Safety Hatches	2 pieces		
Ventilation and Air Conditioning			
Air Conditioning	●		
Electrical system			
Alternator & Battery	Prestolite 140A / 12V 2*200Ah maintenance free		
Wiring System	24V		



XML6125J12 Double Diff (front-mounted engine)

General Data			
Overall Length/Width/Height(mm)	12500X2550X3840mm		
Wheelbase(mm)	5800+1350		
Overhang Front/Rear(mm)	2336/3009		
Angle of Approach/Departure	14°/11°		
Kerb/Gross Vehicle Weight	15,000Kg/18,500Kg		
Turning Circle(m)	≤22m		
Drive Line			
Emission Control	EURO II		
Engine	Cummins L360 20 (diesel)		
Transmission	S6-160,6 gear manual	6DS150T,6 gear manual	ZF6S1610,6 gear manual
Fuel Tank	400L	530L (option)	530L (option)
Chassis			
Front Axle	7T, disc type		
Rear Axle	13T, ratio 4.10, drum type		
Auxiliary Axle	5.5T		
Steering System	Hydraulic power steering		
Brake System	Double-circuit air brake, parking brake		
Auxiliary Brake	2400N/m eddy-current retarder		
Suspension	Multi-spring leaf		
Bodywork			
Bodywork Frame	Integral structure made of rectangular cross section steel tubes		
Front/Rear Panels	Square steel frame + fiber glass skin panel		
Side Panels	High density steel and aluminum sheets,E-coating for whole body		
Door Arrangement	Front	Middle (Option)	
Height of First Step(mm)	390	390	
Seating Capacity	71+1+1 (3+2)	57+1+1 (2+2)	
Roof Safety Hatches	2 pieces		
Ventilation and Air Conditioning			
Air Conditioning	●		
Electrical system			
Alternator & Battery	Prestolite 140A / 12V 2*200Ah maintenance free		
Wiring System	24V		

